

LEGEND

- EXISTING GROUND ELEVATION (FEET) — 600
- SUBGRADE ELEVATION (FEET) (NOTE 4) — 580
- COMPACTED CLAY LINER ELEVATION (FEET) — 585
- LEACHATE COLLECTION SYSTEM ELEVATION (FEET) — 580
- BUTLER COUNTY/HAMILTON COUNTY LINE
- FEMP PROPERTY LINE
- BATTERY LIMIT
- PERIMETER BERM BASELINE
- LEACHATE TRANSMISSION SYSTEM GRAVITY LINE
- LEACHATE TRANSMISSION SYSTEM MANHOLES (LDS AND LCS) AND HORIZONTAL MONITORING WELL COVER SLAB
- LEACHATE TRANSMISSION SYSTEM PERMANENT LIFT STATION
- (1) CELL DESIGNATION
- ACCESS CORRIDOR OR REROUTED NORTH ENTRANCE ROAD
- CREST OF LDS
- LIMIT OF LEACHATE COLLECTION SYSTEM DRAINAGE LAYER
- DRAINAGE CHANNEL GRAVITY INLET STRUCTURE AND CULVERT
- DRAINAGE FLOW DIRECTION

NOTES:

1. TOPOGRAPHIC MAP BASED ON 1992 SITE FLYOVER.
2. ELEVATIONS ARE IN FEET ABOVE SEA LEVEL DATUM. (NOTE: "SEA LEVEL DATUM" REFERS TO THE NATIONAL GEODETIC VERTICAL DATUM [NGVD].)
3. GRID COORDINATE SYSTEM CORRESPONDS TO STATE PLANAR NORTH AMERICAN DATUM (NAD) 1983 OHIO SOUTH.
4. SUBGRADE ELEVATIONS CORRESPOND TO THE TOP OF PREPARED SUBGRADE, INCLUDING ANY COMPACTED FILL. CONSTRUCTION CONTROL POINTS FOR SUBGRADE ARE PROVIDED ON DRAWING G-5.
5. CELLS SHALL BE DEVELOPED STARTING WITH CELL 1 AND ENDING WITH CELL 8. THE SCHEDULE OF CELL CONSTRUCTION WILL DEPEND ON THE AVAILABILITY OF IMPACTED MATERIAL FROM THE OPERABLE UNITS.
6. DIMENSIONS SHOWN IN CELL 3 ARE TYPICAL FOR CELLS 1 THROUGH 6. DIMENSIONS SHOWN IN CELL 8 ARE TYPICAL FOR CELLS 7 THROUGH 9.

FINAL DESIGN PACKAGE

REV. NO.	DATE	DESCRIPTION	DES BY	DR BY	CHK BY	RVW BY	APP BY
G	11.10.96	FINAL SUBMITTAL TO EPA	DLVL	JRM	LA	KWC	RB
F	25.06.96	PREFINAL SUBMITTAL TO EPA					

100 50 0 100 200
SCALE IN FEET

FOR INFORMATION ONLY

OWNER/FACILITY:
UNITED STATES DEPARTMENT OF ENERGY
FERNALD ENVIRONMENTAL MANAGEMENT PROJECT

CLIENT:
FERMCO Fernald Environmental Restoration Management Corporation

PROJECT:
ON-SITE DISPOSAL FACILITY 456

TITLE:
LEACHATE COLLECTION SYSTEM GRADING PLAN
24007_2

THIS DRAWING MAY NOT BE ISSUED FOR PROJECT TENDER OR CONSTRUCTION, UNLESS SEALED.

Rudolph Bonaparte
SIGNATURE
5 Oct 1996
DATE

STATE OF OHIO
RUDOLPH BONAPARTE
E-56679
REGISTERED PROFESSIONAL ENGINEER
SEAL

GeoSyntec Consultants
1100 LAKE HEARN DRIVE
ATLANTA, GEORGIA 30342 USA

FERMCO PROJECT NO.:	20100
FERMCO SUBCONTRACT NO.:	95PS005028
FERMCO DRAWING NO.:	90X-6000-G-00020
GEOSYNTEC PROJECT NO.:	GE3900-13.1
GEOSYNTEC DOCUMENT NO.:	F96-G078
SHEET NO.:	G-8
REVISION NO.:	G

M:\GRAPHICS\GE3900-13\F96-G078 Tue Oct 08 10:28:40 1996 FERMCO/DUNN

452



1 / G-5 PLAN (TYPICAL)
TOP OF SUBGRADE AT CELL OUTLET
SCALE: 1" = 5'
XREF: F96X0065



2 / G-6 PLAN (TYPICAL)
TOP OF COMPACTED CLAY LINER AT CELL OUTLET
SCALE: 1" = 5'
XREF: F96X0065



3 / G-7 PLAN (TYPICAL)
TOP OF LDS DRAINAGE LAYER AT CELL OUTLET
SCALE: 1" = 5'
XREF: F96X0067



4 / G-8 PLAN (TYPICAL)
TOP OF LCS DRAINAGE LAYER AT CELL OUTLET
SCALE: 1" = 5'
XREF: F96X0111

LEGEND

2008 ⊕ CONSTRUCTION CONTROL POINT (NOTE 2)

NOTES:

1. CELL OUTLET GRADING PLANS ARE TYPICAL FOR CELLS 1 THROUGH 9.
2. CONSTRUCTION CONTROL POINT TABLES ARE PROVIDED ON DRAWINGS G-38 AND G-39.
3. LCS AND LDS PIPES SHALL BE IN ACCORDANCE WITH SECTION 02605 OF THE OSDF SPECIFICATIONS.
4. SEE DRAWINGS G-24 AND G-25 FOR LINER PENETRATION BOX DETAILS.
5. TRENCH FOR LDS AND LCS PIPES IS NOT SHOWN ON THIS DRAWING FOR CLARITY. TRENCHING AND BACKFILLING FOR LDS AND LCS PIPES SHALL BE IN ACCORDANCE WITH SECTION 02215 OF THE OSDF SPECIFICATIONS.
6. HORIZONTAL MONITORING WELL IS NOT SHOWN ON THIS DRAWING FOR CLARITY. SEE DRAWING G-40 FOR HORIZONTAL MONITORING WELL DETAILS.

REV. NO.	DATE	DESCRIPTION	DES. BY	DR. BY	CHK. BY	RVW. BY	APP. BY
G	11.10.96	FINAL SUBMITTAL TO EPA	DLVL	BD	LA	KWC	RB
F	25.06.96	PREFINAL SUBMITTAL TO EPA					

5 2.5 0 5 10
SCALE IN FEET

FOR INFORMATION ONLY

OWNER/FACILITY:
UNITED STATES DEPARTMENT OF ENERGY
FERNALD ENVIRONMENTAL MANAGEMENT PROJECT

CLIENT:
FERMCO — FERNALD ENVIRONMENTAL RESTORATION MANAGEMENT CORPORATION

PROJECT:
ON-SITE DISPOSAL FACILITY

TITLE:
CELL OUTLET GRADING PLANS 457
240617-2

THIS DRAWING MAY NOT BE ISSUED FOR PROJECT TENDER OR CONSTRUCTION, UNLESS SEALED.

STATE OF OHIO — RUDOLPH BONAPARTE — E-56679 — REGISTERED PROFESSIONAL ENGINEER

Rudolph Bonaparte
SIGNATURE
8 Oct 1996
DATE

GeoSyntec Consultants
1100 LAKE HEARN DRIVE
ATLANTA, GEORGIA 30342 USA

FERMCO PROJECT NO.:	20100
FERMCO SUBCONTRACT NO.:	95PS005028
FERMCO DRAWING NO.:	90X-6000-G-00021
GEOSYNTEC PROJECT NO.:	GE3900-13.1
GEOSYNTEC DOCUMENT NO.:	F96-G053
SHEET NO.:	G-9
REVISION NO.:	G

FINAL DESIGN PACKAGE

M:\GAGA\DOC\GE3900--13\F96-G053 Sat Oct 05 10:52:01 1996 John C.

FINAL DESIGN PACKAGE

LEGEND

- EXISTING GROUND ELEVATION (FEET) — 600
- SUBGRADE ELEVATION (FEET) (NOTE 4) — 580
- COMPACTED CLAY LINER ELEVATION (FEET) — 585
- CONTOURING LAYER ELEVATION (FEET) — 585
- BUTLER COUNTY/HAMILTON COUNTY LINE
- FEMP PROPERTY LINE
- BATTERY LIMIT
- IMPACTED MATERIAL DISPOSAL LIMIT
- PERIMETER BERM BASELINE
- LEACHATE TRANSMISSION SYSTEM GRAVITY LINE
- LEACHATE TRANSMISSION SYSTEM MANHOLES (LDS AND LCS) AND HORIZONTAL MONITORING WELL COVER SLAB
- LEACHATE TRANSMISSION SYSTEM PERMANENT LIFT STATION
- ACCESS CORRIDOR OR REROUTED NORTH ENTRANCE ROAD
- CREST OF LEAK DETECTION SYSTEM DRAINAGE LAYER
- CREST OF LEACHATE COLLECTION SYSTEM DRAINAGE LAYER
- LIMIT OF CONTOURING LAYER
- DRAINAGE CHANNEL GRAVITY INLET STRUCTURE AND CULVERT
- DRAINAGE FLOW DIRECTION
- 5010 — CONSTRUCTION CONTROL POINT (NOTE 6)

NOTES:

1. TOPOGRAPHIC MAP BASED ON 1992 SITE FLYOVER.
2. ELEVATIONS ARE IN FEET ABOVE SEA LEVEL DATUM. (NOTE: "SEA LEVEL DATUM" REFERS TO THE NATIONAL GEODETIC VERTICAL DATUM [NGVD])
3. GRID COORDINATE SYSTEM CORRESPONDS TO STATE PLANAR NORTH AMERICAN DATUM (NAD) 1983 OHIO SOUTH.
4. SUBGRADE ELEVATIONS CORRESPOND TO THE TOP OF PREPARED SUBGRADE, INCLUDING ANY COMPACTED FILL. CONSTRUCTION CONTROL POINTS FOR SUBGRADE ARE PROVIDED ON DRAWING G-5.
5. CELLS SHALL BE DEVELOPED STARTING WITH CELL 1 AND ENDING WITH CELL 8. THE SCHEDULE OF CELL CONSTRUCTION WILL DEPEND ON THE AVAILABILITY OF IMPACTED MATERIAL FROM THE OPERABLE UNITS.
6. CONSTRUCTION CONTROL POINT TABLES ARE PROVIDED ON DRAWINGS G-38 AND G-39.



REV. NO.	DATE	DESCRIPTION	DES BY	DR BY	CHK BY	RVW BY	APP BY
F	25.06.96	PRELIMINARY SUBMITTAL TO EPA					
G	11.10.96	FINAL SUBMITTAL TO EPA	DLL	JSM	LA	KWC	RB

FOR INFORMATION ONLY

OWNER/FACILITY:
UNITED STATES DEPARTMENT OF ENERGY
FERNALD ENVIRONMENTAL MANAGEMENT PROJECT

CLIENT:
FERMCO
FERNALD ENVIRONMENTAL RESTORATION MANAGEMENT CORPORATION
Restoration Management Corporation

PROJECT:
ON-SITE DISPOSAL FACILITY

TITLE:
CONTOURING LAYER GRADING PLAN

458

d40017_3

FEMPO PROJECT NO.: 20100
FEMPO SUBCONTRACT NO.: 95P500502G28
FEMPO DRAWING NO.: 90X-6000-G-00028
GEOSYNTEC PROJECT NO.: GE3300-13.1
GEOSYNTEC DOCUMENT NO.: P96-0087
SHEET NO.: G-10
REVISION NO.: G

THIS DRAWING MAY NOT BE ISSUED FOR PRODUCTION PRIOR TO CONSTRUCTION, UNLESS SEALED.

REGISTERED RUDOLPH BOUNAPARTE E-56679 STATE OF OHIO PROFESSIONAL ENGINEER

Rudolph Bounaparte
SIGNATURE
5.01.1996
DATE

GeoSyntec CONSULTANTS
1100 LAKE HEARN DRIVE
ATLANTA, GEORGIA 30342 USA

M:\GA\A2D2\GE3300\-13\F96-0087 Tue, Oct 08 10:53:56 1996 FERMCO\DRAWN

452



LEGEND

- 600 — EXISTING GROUND ELEVATION (FEET)
- 595 — FINISHED GRADE ELEVATION (FEET)
- BUTLER COUNTY/HAMILTON COUNTY LINE
- FEMP PROPERTY LINE
- BATTERY LIMIT
- BASELINE OR CENTERLINE
- LEACHATE TRANSMISSION SYSTEM GRAVITY LINE
- LEACHATE TRANSMISSION SYSTEM MANHOLES (LDS AND LCS) AND HORIZONTAL MONITORING WELL COVER SLAB
- LEACHATE TRANSMISSION SYSTEM PERMANENT LIFT STATION
- ACCESS CORRIDOR OR REROUTED NORTH ENTRANCE ROAD
- DRAINAGE CHANNEL GRAVITY INLET STRUCTURE AND CULVERT
- DRAINAGE FLOW DIRECTION
- 6010 — CONSTRUCTION CONTROL POINT (NOTE 5)

NOTES:

1. TOPOGRAPHIC MAP BASED ON 1992 SITE FLYOVER.
2. ELEVATIONS ARE IN FEET ABOVE SEA LEVEL DATUM. (NOTE: "SEA LEVEL DATUM" REFERS TO THE NATIONAL GEODETIC VERTICAL DATUM [NGVD].)
3. GRID COORDINATE SYSTEM CORRESPONDS TO STATE PLANAR NORTH AMERICAN DATUM (NAD) 1983 OHIO SOUTH.
4. CELLS SHALL BE DEVELOPED STARTING WITH CELL 1 AND ENDING WITH CELL 8. THE SCHEDULE OF CELL CONSTRUCTION WILL DEPEND ON THE AVAILABILITY OF IMPACTED MATERIAL FROM THE OPERABLE UNITS.
5. CONSTRUCTION CONTROL POINT TABLES ARE PROVIDED ON DRAWINGS G-38 AND G-39.

REV. NO.	DATE	DESCRIPTION	DES BY	DR BY	CHK BY	RVW BY	APP BY
G	11.10.96	FINAL SUBMITTAL TO EPA	DLVL	JRM	LA	KWC	RB
F	25.06.96	PREFINAL SUBMITTAL TO EPA					

100 50 0 100 200
SCALE IN FEET

FOR INFORMATION ONLY

OWNER/FACILITY:
UNITED STATES DEPARTMENT OF ENERGY
FERNALD ENVIRONMENTAL MANAGEMENT PROJECT

CLIENT:
FERMCO — FERNALD ENVIRONMENTAL RESTORATION MANAGEMENT CORPORATION

PROJECT:
ON-SITE DISPOSAL FACILITY

TITLE:
FINAL COVER SYSTEM GRADING PLAN 459
24001-4

THIS DRAWING MAY NOT BE ISSUED FOR PROJECT TENDER OR CONSTRUCTION, UNLESS SEALED.

Rudolph Bonaparte
SIGNATURE
5 Oct 1996
DATE

STATE OF OHIO — RUDOLPH BONAPARTE — E-56679 — REGISTERED PROFESSIONAL ENGINEER — SEAL

GeoSyntec Consultants
1100 LAKE HEARN DRIVE
ATLANTA, GEORGIA 30342 USA

FERMCO PROJECT NO.:	20100
FERMCO SUBCONTRACT NO.:	95PS005028
FERMCO DRAWING NO.:	90X-6000-G-00023
GEOSYNTEC PROJECT NO.:	GE3900-13.1
GEOSYNTEC DOCUMENT NO.:	F96-6081
SHEET NO.:	G-11
REVISION NO.:	G

FINAL DESIGN PACKAGE

M:\GACAD2\GE3900-.13\F96-6081 Tue Oct 08 10:57:34 1996 ADENA





D / G-12 SECTION
BORROW AREA CULVERT
SCALE: 1" = 10' (NOTE 6)

LEGEND

- 600 — EXISTING GROUND ELEVATION (FEET)
- 570 — FINISHED GRADE ELEVATION (FEET)
- FEMP PROPERTY LINE
- BATTERY LIMIT
- BORROW AREA LIMIT
- DRAINAGE FLOW DIRECTION
- ACCESS CORRIDOR OR REROUTED NORTH ENTRANCE ROAD
- 6050 CONSTRUCTION CONTROL POINT (NOTE 4)

NOTES:

1. TOPOGRAPHIC MAP BASED ON 1992 SITE FLYOVER.
2. ELEVATIONS ARE IN FEET ABOVE SEA LEVEL DATUM. (NOTE: "SEA LEVEL DATUM" REFERS TO THE NATIONAL GEODETIC VERTICAL DATUM [NGVD].)
3. GRID COORDINATE SYSTEM CORRESPONDS TO STATE PLANAR NORTH AMERICAN DATUM (NAD) 1983 OHIO SOUTH.
4. CONSTRUCTION CONTROL POINT TABLES ARE PROVIDED ON DRAWINGS G-38 AND G-39.
5. SIZE AND MATERIAL OF CULVERT MAY BE REVISED BASED ON THE INSTALLATION METHOD REQUIRED TO NOT INTERRUPT TRAFFIC FLOW ON THE SOUTH ENTRANCE ROAD. REVISIONS MADE TO THE CULVERT SHALL NOT CHANGE THE DESIGN DISCHARGE FROM A 48-INCH ACCMP.
6. DETAILS ARE SHOWN TO SCALE AS NOTED EXCEPT FOR THE GEOSYNTHETICS WHICH ARE SHOWN AT AN EXAGGERATED SCALE FOR CLARITY. MATERIAL TOLERANCES SHALL BE WITHIN THE LIMITS GIVEN IN THE OSDF SPECIFICATIONS.

REV. NO.	DATE	DESCRIPTION	DES BY	DR BY	CHK BY	RVW BY	APP BY
G	11.10.96	FINAL SUBMITTAL TO EPA	DLVL	RD	LA	KWC	RB
F	25.06.96	PREFINAL SUBMITTAL TO EPA					

100 50 0 100 200
SCALE IN FEET

FOR INFORMATION ONLY

OWNER/FACILITY:
UNITED STATES DEPARTMENT OF ENERGY
FERNALD ENVIRONMENTAL MANAGEMENT PROJECT

CLIENT:
FERMCO — FERNALD ENVIRONMENTAL RESTORATION MANAGEMENT CORPORATION

PROJECT:
ON-SITE DISPOSAL FACILITY

TITLE:
BORROW AREA RESTORATION PLAN 460
24007_5

THIS DRAWING MAY NOT BE ISSUED FOR PROJECT TENDER OR CONSTRUCTION, UNLESS SEALED.

Rudolph Bonaparte
SIGNATURE
5 Oct 1996
DATE

STATE OF OHIO — RUDOLPH BONAPARTE — E-56679 — REGISTERED PROFESSIONAL ENGINEER

GeoSyntec Consultants
1100 LAKE HEARN DRIVE
ATLANTA, GEORGIA 30342 USA

FERMCO PROJECT NO.:	20100
FERMCO SUBCONTRACT NO.:	95PS005028
FERMCO DRAWING NO.:	90X-6000-G-00024
GEOSYNTEC PROJECT NO.:	GE3900-13.1
GEOSYNTEC DOCUMENT NO.:	F96-G010
SHEET NO.:	G-12
REVISION NO.:	G

FINAL DESIGN PACKAGE

M:\GAC\A02\GE3900-13\F96-G010 Fri Oct 04 11:19:48 1996 FERMCO\DLMN

452





A G-11 **SECTION NORTH-SOUTH**
HORIZONTAL SCALE: 1" = 100'
VERTICAL SCALE: 1" = 10'

NOTES:

1. EXISTING GROUND ELEVATIONS BASED ON 1992 SITE FLYOVER.
2. ELEVATIONS ARE IN FEET ABOVE SEA LEVEL DATUM. (NOTE: "SEA LEVEL DATUM" REFERS TO THE NATIONAL GEODETIC VERTICAL DATUM [NGVD].)
3. A MINIMUM THICKNESS OF 3 FEET OF SELECT IMPACTED MATERIAL SHALL BE PLACED ABOVE THE PROTECTIVE LAYER AND BELOW THE CONTOURING LAYER. THIS THICKNESS MAY BE REDUCED TO 2 FEET ABOVE THE PROTECTIVE LAYER IF THE FIRST LIFT OF IMPACTED MATERIAL PLACEMENT IS CATEGORY 1 OR 2 MATERIAL AS DEFINED BY THE OSDF IMPACTED MATERIAL PLACEMENT (IMP) PLAN. ALL IMPACTED MATERIAL SHALL BE PLACED IN ACCORDANCE WITH SECTION 13010 OF THE OSDF SPECIFICATIONS AND THE IMP PLAN.
4. CELLS SHALL BE DEVELOPED STARTING WITH CELL 1 AND ENDING WITH CELL 8. THE SCHEDULE OF CELL CONSTRUCTION WILL DEPEND ON THE AVAILABILITY OF IMPACTED MATERIAL FROM THE OPERABLE UNITS.
5. CONTINGENCY CELL WILL ONLY BE CONSTRUCTED IF NEEDED. CONTINGENCY CELL VOLUME IS PROVIDED TO ACCOUNT FOR OVEREXCAVATION OF IMPACTED MATERIAL AND/OR IDENTIFICATION OF ADDITIONAL VOLUME OF IMPACTED MATERIAL AS A RESULT OF CONFIRMATORY SAMPLING ACTIVITIES. ONLY ON-SITE MATERIAL SATISFYING THE OSDF WASTE ACCEPTANCE CRITERIA WILL BE DISPOSED IN THE OSDF. IF THE CONTINGENCY CELL IS NOT DEVELOPED, THE SOUTHERN LIMIT OF THE OSDF WILL MOVE 400 FEET TO THE NORTH.

FINAL DESIGN PACKAGE

FOR INFORMATION ONLY

REV. NO.	DATE	DESCRIPTION	DES BY	DR BY	CHK BY	RVW BY	APP BY
G	11.10.96	FINAL SUBMITTAL TO EPA	DLVL	JRM	LA	KWC	RB
F	25.06.96	PREFINAL SUBMITTAL TO EPA					

100 50 0 100 200 SCALE IN FEET
10 5 0 10 20 SCALE IN FEET

OWNER/FACILITY:
UNITED STATES DEPARTMENT OF ENERGY
FERNALD ENVIRONMENTAL MANAGEMENT PROJECT

CLIENT:
FERMCO FERNALD ENVIRONMENTAL RESTORATION MANAGEMENT CORPORATION

PROJECT:
ON-SITE DISPOSAL FACILITY

TITLE:
NORTH-SOUTH SECTION 461
24D017-6

THIS DRAWING MAY NOT BE ISSUED FOR PROJECT TENDER OR CONSTRUCTION, UNLESS SEALED.

Rudolph Bonaparte SIGNATURE
5 Oct 1996 DATE

STATE OF OHIO RUDOLPH BONAPARTE E-56679 REGISTERED PROFESSIONAL ENGINEER

GeoSyntec Consultants
1100 LAKE HEARN DRIVE ATLANTA, GEORGIA 30342 USA

FERMCO PROJECT NO.:	20100
FERMCO SUBCONTRACT NO.:	95PS005028
FERMCO DRAWING NO.:	90X-6000-G-00025
GEOSYNTEC PROJECT NO.:	GE3900-13.1
GEOSYNTEC DOCUMENT NO.:	F96-G020
SHEET NO.:	G-15
REVISION NO.:	G

M:\GACAD2CE\GE3900\-13\F96-G020 Fri Oct 04 10:23:28 1996 FERMCO/DWN

452





B / G-11 SECTION
WEST-EAST AT CELL 1 AND CELL 2 INTERCELL BERM
HORIZONTAL SCALE: 1" = 30'
VERTICAL SCALE: 1" = 10'
XREF: F961044

NOTES:

1. EXISTING GROUND ELEVATIONS BASED ON 1992 SITE FLYOVER.
2. ELEVATIONS ARE IN FEET ABOVE SEA LEVEL DATUM. (NOTE: "SEA LEVEL DATUM" REFERS TO THE NATIONAL GEODETIC VERTICAL DATUM [NGVD].)
3. A MINIMUM THICKNESS OF 3 FEET OF SELECT IMPACTED MATERIAL SHALL BE PLACED ABOVE THE PROTECTIVE LAYER AND BELOW THE CONTOURING LAYER. THIS THICKNESS MAY BE REDUCED TO 2 FEET ABOVE THE PROTECTIVE LAYER IF THE FIRST LIFT OF IMPACTED MATERIAL PLACEMENT IS CATEGORY 1 OR 2 MATERIAL AS DEFINED BY THE OSDF IMPACTED MATERIAL PLACEMENT (IMP) PLAN. ALL IMPACTED MATERIAL SHALL BE PLACED IN ACCORDANCE WITH SECTION 13010 OF THE OSDF SPECIFICATIONS AND THE IMP PLAN.
4. DETAILS ARE SHOWN TO SCALE AS NOTED EXCEPT FOR THE GEOSYNTHETICS WHICH ARE SHOWN AT AN EXAGGERATED SCALE FOR CLARITY. MATERIAL TOLERANCES SHALL BE WITHIN THE LIMITS GIVEN IN THE OSDF SPECIFICATIONS.

FINAL DESIGN PACKAGE

FOR INFORMATION ONLY

REV. NO.	DATE	DESCRIPTION	DES BY	DR BY	CHK BY	RVW BY	APP BY
G	11.10.96	FINAL SUBMITTAL TO EPA	DLVL	JRM	LA	KWC	RB
F	25.06.96	PREFINAL SUBMITTAL TO EPA					

30 15 0 30 60 SCALE IN FEET
10 5 0 10 20 SCALE IN FEET

OWNER/FACILITY:
UNITED STATES DEPARTMENT OF ENERGY
FERNALD ENVIRONMENTAL MANAGEMENT PROJECT

CLIENT:
FERMCO Fernald Environmental Restoration Management Corporation
FERNALD ENVIRONMENTAL RESTORATION MANAGEMENT CORPORATION

PROJECT:
ON-SITE DISPOSAL FACILITY

TITLE:
WEST-EAST SECTION AT CELL 1 AND CELL 2 INTERCELL BERM 462
24001-7

THIS DRAWING MAY NOT BE ISSUED FOR PROJECT TENDER OR CONSTRUCTION, UNLESS SEALED.

Rudolph Bonaparte
SIGNATURE
5 Oct 1996
DATE

STATE OF OHIO
RUDOLPH BONAPARTE
E-56679
REGISTERED PROFESSIONAL ENGINEER

GeoSyntec Consultants
1100 LAKE HEARN DRIVE
ATLANTA, GEORGIA 30342 USA

FERMCO PROJECT NO.:	20100
FERMCO SUBCONTRACT NO.:	95PS005028
FERMCO DRAWING NO.:	90X-6000-G-00026
GEOSYNTEC PROJECT NO.:	GE3900-13.1
GEOSYNTEC DOCUMENT NO.:	F96-0022
SHEET NO.:	G-16
REVISION NO.:	G

M:\GACADD\GE3900-13\F96-0022 Fri Oct 04 10:08:58 1996 FERMCO\DANN

452





C / G-11 SECTION
WEST-EAST AT CELL 4 BASE
HORIZONTAL SCALE: 1" = 30'
VERTICAL SCALE: 1" = 10'

NOTES:

1. EXISTING GROUND ELEVATIONS BASED ON 1992 SITE FLYOVER.
2. ELEVATIONS ARE IN FEET ABOVE SEA LEVEL DATUM. (NOTE: "SEA LEVEL DATUM" REFERS TO THE NATIONAL GEODETIC VERTICAL DATUM [NGVD].)
3. A MINIMUM THICKNESS OF 3 FEET OF SELECT IMPACTED MATERIAL SHALL BE PLACED ABOVE THE PROTECTIVE LAYER AND BELOW THE CONTOURING LAYER. THIS THICKNESS MAY BE REDUCED TO 2 FEET ABOVE THE PROTECTIVE LAYER IF THE FIRST LIFT OF IMPACTED MATERIAL PLACEMENT IS CATEGORY 1 OR 2 MATERIAL AS DEFINED BY THE OSDF IMPACTED MATERIAL PLACEMENT (IMP) PLAN. ALL IMPACTED MATERIAL SHALL BE PLACED IN ACCORDANCE WITH SECTION 13010 OF THE OSDF SPECIFICATIONS AND THE IMP PLAN.
4. DETAILS ARE SHOWN TO SCALE AS NOTED EXCEPT FOR THE GEOSYNTHETICS WHICH ARE SHOWN AT AN EXAGGERATED SCALE FOR CLARITY. MATERIAL TOLERANCES SHALL BE WITHIN THE LIMITS GIVEN IN THE OSDF SPECIFICATIONS.

FINAL DESIGN PACKAGE

REV. NO.	DATE	DESCRIPTION	DES BY	DR BY	CHK BY	RVW BY	APP BY
G	11.10.96	FINAL SUBMITTAL TO EPA	DLVL	JRM	LA	KWC	RB
F	25.06.96	PREFINAL SUBMITTAL TO EPA					

30 15 0 30 60 SCALE IN FEET
10 5 0 10 20 SCALE IN FEET

INFORMATION ONLY

OWNER/FACILITY:
UNITED STATES DEPARTMENT OF ENERGY
FERNALD ENVIRONMENTAL MANAGEMENT PROJECT

CLIENT:
Fernald Environmental Restoration Management Corporation
FERNALD ENVIRONMENTAL RESTORATION MANAGEMENT CORPORATION

PROJECT:
ON-SITE DISPOSAL FACILITY

TITLE:
WEST-EAST SECTION AT CELL 4 BASE 463
240017.8

THIS DRAWING MAY NOT BE ISSUED FOR PROJECT TENDER OR CONSTRUCTION, UNLESS SEALED.

STATE OF OHIO
RUDOLPH BONAPARTE
E-56879
REGISTERED PROFESSIONAL ENGINEER
SEAL

Rudolph Bonaparte
SIGNATURE
8 Oct 1996
DATE

GeoSyntec Consultants
1100 LAKE HEARN DRIVE
ATLANTA, GEORGIA 30342 USA

FERMCO PROJECT NO.:	20100
FERMCO SUBCONTRACT NO.:	95PS005028
FERMCO DRAWING NO.:	90X-6000-G-00027
GEOSYNTEC PROJECT NO.:	GE3900-13.1
GEOSYNTEC DOCUMENT NO.:	F96-G023
SHEET NO.:	G-17
REVISION NO.:	G

M:\GACAD\GE3900\-13\F96-G023 Sat Oct 05 09:46:51 1996 FERMCO\DWN

452





D G-11 **SECTION**
WEST–EAST AT CELL 7 DRAINAGE CORRIDOR
HORIZONTAL SCALE: 1" = 30'
VERTICAL SCALE: 1" = 10'
REF: FM60045

FOR INFORMATION ONLY

NOTES:

1. EXISTING GROUND ELEVATIONS BASED ON 1992 SITE FLYOVER.
2. ELEVATIONS ARE IN FEET ABOVE SEA LEVEL DATUM. (NOTE: "SEA LEVEL DATUM" REFERS TO THE NATIONAL GEODETIC VERTICAL DATUM [NGVD].)
3. A MINIMUM THICKNESS OF 3 FEET OF SELECT IMPACTED MATERIAL SHALL BE PLACED ABOVE THE PROTECTIVE LAYER AND BELOW THE CONTOURING LAYER. THIS THICKNESS MAY BE REDUCED TO 2 FEET ABOVE THE PROTECTIVE LAYER IF THE FIRST LIFT OF IMPACTED MATERIAL PLACEMENT IS CATEGORY 1 OR 2 MATERIAL AS DEFINED BY THE OSDF IMPACTED MATERIAL PLACEMENT (IMP) PLAN. ALL IMPACTED MATERIAL SHALL BE PLACED IN ACCORDANCE WITH SECTION 13010 OF THE OSDF SPECIFICATIONS AND THE IMP PLAN.
4. LCS AND LDS PIPES SHALL BE IN ACCORDANCE WITH SECTION 02605 OF THE OSDF SPECIFICATIONS AND TERMINATE AT THE UPGRADIENT END OF THE DRAINAGE CORRIDOR WITH A 6-INCH MOLDED END CAP. (LDS PIPE NOT SHOWN IN THIS SECTION.)
5. DETAILS ARE SHOWN TO SCALE AS NOTED EXCEPT FOR THE GEOSYNTHETICS WHICH ARE SHOWN AT AN EXAGGERATED SCALE FOR CLARITY. MATERIAL TOLERANCES SHALL BE WITHIN THE LIMITS GIVEN IN THE OSDF SPECIFICATIONS.

FINAL DESIGN PACKAGE

REV. NO.	DATE	DESCRIPTION	DES BY	DR BY	CHK BY	RVW BY	APP BY
G	11.10.96	FINAL SUBMITTAL TO EPA	DLVL	JRM	LA	KWC	RB
F	25.06.96	PREFINAL SUBMITTAL TO EPA					

30 15 0 30 60 SCALE IN FEET
10 5 0 10 20 SCALE IN FEET

OWNER/FACILITY:
UNITED STATES DEPARTMENT OF ENERGY
FERNALD ENVIRONMENTAL MANAGEMENT PROJECT
CLIENT:
FERMCO Environmental Restoration Management Corporation
FERNALD ENVIRONMENTAL RESTORATION MANAGEMENT CORPORATION
PROJECT:
ON-SITE DISPOSAL FACILITY
TITLE:
WEST-EAST SECTION AT CELL 7 DRAINAGE CORRIDOR
24017-9
464

THIS DRAWING MAY NOT BE ISSUED FOR PROJECT TENDER OR CONSTRUCTION, UNLESS SEALED.
STATE OF OHIO RUDOLPH BONAPARTE E-56679 REGISTERED PROFESSIONAL ENGINEER
Rudolph Bonaparte SIGNATURE
5 Oct 1996 DATE

GeoSyntec Consultants
1100 LAKE HEARN DRIVE ATLANTA, GEORGIA 30342 USA

FERMCO PROJECT NO.:	20100
FERMCO SUBCONTRACT NO.:	95P5005028
FERMCO DRAWING NO.:	90X-6000-G-00028
GEOSYNTEC PROJECT NO.:	GE3900-13.1
GEOSYNTEC DOCUMENT NO.:	F96-0021
SHEET NO.:	G-18
REVISION NO.:	G

K:\GAC\DOC\GE3900-13\F96-0021 Fri Oct 04 09:48:07 1996 FERMCO\DWN

452



A G-12 **SECTION BORROW AREA**
HORIZONTAL SCALE: 1" = 60'
VERTICAL SCALE: 1" = 10'



B G-12 **SECTION BORROW AREA**
HORIZONTAL SCALE: 1" = 60'
VERTICAL SCALE: 1" = 10'



C G-12 **SECTION BORROW AREA**
HORIZONTAL SCALE: 1" = 60'
VERTICAL SCALE: 1" = 10'



5A G-12 **DETAIL ANTI-SEEP COLLAR**
SCALE: NTS
XREF: FS6XC414



6 G-12 **DETAIL DRAINAGE CHANNEL 3**
SCALE: 1" = 5'
XREF: FS6XF402



5 G-12 **DETAIL (TYPICAL) DRAINAGE CHANNEL 1 AND 2**
SCALE: 1" = 5'
XREF: FS6XF406

NOTES:

1. EXISTING GROUND ELEVATIONS BASED ON 1992 SITE FLYOVER.
2. ELEVATIONS ARE IN FEET ABOVE SEA LEVEL DATUM. (NOTE: "SEA LEVEL DATUM" REFERS TO THE NATIONAL GEODETIC VERTICAL DATUM [NGVD].)
3. CONSTRUCTION CONTROL POINT TABLES FOR BORROW AREA PROVIDED ON DRAWING G-39.

FINAL DESIGN PACKAGE

FOR INFORMATION ONLY

REV. NO.	DATE	DESCRIPTION	DES BY	DR BY	CHK BY	RVW BY	APP BY
G	11.10.96	FINAL SUBMITTAL TO EPA	DLVL	RD	LA	KWC	RB
F	25.06.96	PREFINAL SUBMITTAL TO EPA					

60 30 0 60 120 SCALE IN FEET
10 5 0 10 20 SCALE IN FEET

OWNER/FACILITY:
UNITED STATES DEPARTMENT OF ENERGY
FERNALD ENVIRONMENTAL MANAGEMENT PROJECT

CLIENT:
FERMCO — FERNALD ENVIRONMENTAL RESTORATION MANAGEMENT CORPORATION

PROJECT:
ON-SITE DISPOSAL FACILITY

TITLE:
BORROW AREA SECTIONS AND DETAILS

24D017_10

465

THIS DRAWING MAY NOT BE ISSUED FOR PROJECT TENDER OR CONSTRUCTION, UNLESS SEALED.

STATE OF OHIO — RUDOLPH BONAPARTE — E-56679 — REGISTERED PROFESSIONAL ENGINEER

Rudolph Bonaparte
SIGNATURE
8 Oct 1996
DATE

GeoSyntec Consultants
1100 LAKE HEARN DRIVE
ATLANTA, GEORGIA 30342 USA

FERMCO PROJECT NO.:	20100
FERMCO SUBCONTRACT NO.:	95PS005028
FERMCO DRAWING NO.:	90X-6000-G-00029
GEOSYNTEC PROJECT NO.:	GE3900-13.1
GEOSYNTEC DOCUMENT NO.:	F96-G061
SHEET NO.:	G-19
REVISION NO.:	G

H:\F96-G061 Mon Oct 07 17:34:05 1996 J.MILLER



7 G-15 **DETAIL**
NORTH PERIMETER AFTER OSDF CLOSURE
SCALE: 1" = 8'
REF: 756H3304





8 – **DETAIL**
NORTHWEST CORNER AFTER OSDF CLOSURE
SCALE: 1" = 8'
REF: 756H3302



9 G-15 **DETAIL**
SOUTH PERIMETER AFTER OSDF CLOSURE
SCALE: 1" = 8'
REF: 756H3335

NOTES:

1. DETAILS ARE SHOWN TO SCALE AS NOTED EXCEPT FOR THE GEOSYNTHETICS WHICH ARE SHOWN AT AN EXAGGERATED SCALE FOR CLARITY. MATERIAL TOLERANCES SHALL BE WITHIN THE LIMITS GIVEN IN THE OSDF SPECIFICATIONS.
2. A MINIMUM THICKNESS OF 3 FEET OF SELECT IMPACTED MATERIAL SHALL BE PLACED ABOVE THE PROTECTIVE LAYER AND BELOW THE CONTOURING LAYER. THIS THICKNESS MAY BE REDUCED TO 2 FEET ABOVE THE PROTECTIVE LAYER IF THE FIRST LIFT OF IMPACTED MATERIAL PLACEMENT IS CATEGORY 1 OR 2 MATERIAL AS DEFINED BY THE OSDF IMPACTED MATERIAL PLACEMENT (IMP) PLAN. ALL IMPACTED MATERIAL SHALL BE PLACED IN ACCORDANCE WITH SECTION 13010 OF THE OSDF SPECIFICATIONS AND THE IMP PLAN.
3. CONSTRUCTION CONTROL POINT TABLES ARE PROVIDED ON DRAWINGS G-38 AND G-39.

REV. NO.	DATE	DESCRIPTION	DES BY	DR BY	CHK BY	RVW BY	APP BY
G	11.10.96	FINAL SUBMITTAL TO EPA	DLVL	JRM	LA	KWC	RB
F	25.06.96	PREFINAL SUBMITTAL TO EPA					

SCALE AS SHOWN

FOR INFORMATION ONLY

OWNER/FACILITY:
UNITED STATES DEPARTMENT OF ENERGY
FERNALD ENVIRONMENTAL MANAGEMENT PROJECT

CLIENT:
FERMCO Fernald Environmental Restoration Management Corporation
FERNALD ENVIRONMENTAL RESTORATION MANAGEMENT CORPORATION

PROJECT:
ON-SITE DISPOSAL FACILITY

TITLE:
CELL PERIMETER DETAILS I

24007-77

466

THIS DRAWING MAY NOT BE ISSUED FOR PROJECT TENDER OR CONSTRUCTION, UNLESS SEALED.

STATE OF OHIO RUDOLPH BONAPARTE E-58579 REGISTERED PROFESSIONAL ENGINEER

Rudolph Bonaparte
SIGNATURE

5 Oct 1996
DATE

GEO SYNTEC CONSULTANTS
1100 LAKE HEARN DRIVE
ATLANTA, GEORGIA 30342 USA

FERMCO PROJECT NO.:	20100
FERMCO SUBCONTRACT NO.:	95PS005028
FERMCO DRAWING NO.:	90X-6000-G-00030
GEOSYNTEC PROJECT NO.:	GE3900-13.1
GEOSYNTEC DOCUMENT NO.:	FS6-G137
SHEET NO.:	G-20
REVISION NO.:	G

FINAL DESIGN PACKAGE

M:\GACAD02\GE3900-13\FS0-G137 Fri Oct 04 10:37:29 1996 FERMCO/DUNN



10 G-17 **DETAIL**
EAST PERIMETER AFTER OSDF CLOSURE
SCALE: 1" = 8'



11 G-17 **DETAIL**
WEST PERIMETER AFTER OSDF CLOSURE
SCALE: 1" = 8'



12 - **DETAIL**
TYPICAL CORNER AFTER OSDF CLOSURE
SCALE: 1" = 8'

NOTES:

1. DETAILS ARE SHOWN TO SCALE AS NOTED EXCEPT FOR THE GEOSYNTHETICS WHICH ARE SHOWN AT AN EXAGGERATED SCALE FOR CLARITY. MATERIAL TOLERANCES SHALL BE WITHIN THE LIMITS GIVEN IN THE OSDF SPECIFICATIONS.
2. A MINIMUM THICKNESS OF 3 FEET OF SELECT IMPACTED MATERIAL SHALL BE PLACED ABOVE THE PROTECTIVE LAYER AND BELOW THE CONTOURING LAYER. THIS THICKNESS MAY BE REDUCED TO 2 FEET ABOVE THE PROTECTIVE LAYER IF THE FIRST LIFT OF IMPACTED IMPACTED MATERIAL PLACEMENT IS CATEGORY 1 OR 2 MATERIAL AS DEFINED BY THE OSDF IMPACTED MATERIAL PLACEMENT (IMP) PLAN. ALL IMPACTED MATERIAL SHALL BE PLACED IN ACCORDANCE WITH SECTION 13010 OF THE OSDF SPECIFICATIONS AND THE IMP PLAN.
3. CONSTRUCTION CONTROL POINT TABLES PROVIDED ON DRAWINGS G-38 AND G-39.

REV. NO.	DATE	DESCRIPTION	DES. BY	DR. BY	CHK. BY	RVW. BY	APP. BY
G	11.10.96	FINAL SUBMITTAL TO EPA	DLVL	RD	LA	KWC	RB
F	25.06.96	PREFINAL SUBMITTAL TO EPA					

SCALE AS SHOWN

FOR INFORMATION ONLY

OWNER/FACILITY:
UNITED STATES DEPARTMENT OF ENERGY
FERNALD ENVIRONMENTAL MANAGEMENT PROJECT

CLIENT:
FERMCO FERNALD ENVIRONMENTAL RESTORATION MANAGEMENT CORPORATION

PROJECT:
ON-SITE DISPOSAL FACILITY

TITLE:
CELL PERIMETER DETAILS II

467
240017.12

THIS DRAWING MAY NOT BE ISSUED FOR PROJECT TENDER OR CONSTRUCTION, UNLESS SEALED.

STATE OF OHIO
RUDOLPH BONAPARTE
E-56579
REGISTERED PROFESSIONAL ENGINEER

Rudolph Bonaparte
SIGNATURE
5 Oct 1996
DATE

GeoSyntec Consultants
1100 LAKE HEARN DRIVE
ATLANTA, GEORGIA 30342 USA

FERMCO PROJECT NO.:	20100
FERMCO SUBCONTRACT NO.:	95P5005028
FERMCO DRAWING NO.:	90X-6000-G-00031
GEOSYNTEC PROJECT NO.:	GE3900-13.1
GEOSYNTEC DOCUMENT NO.:	F96-G138
SHEET NO.:	G-21
REVISION NO.:	G

FINAL DESIGN PACKAGE

M:\GA\CAD\DCVGE3900\p-13\F96-G138 Fri Oct 04 10:51:32 1996 FERMCO\TRANN



13 / G-15 **DETAIL**
LINER SYSTEM
SCALE: 1" = 2'



14 / G-20 **DETAIL**
LINER SYSTEM ANCHOR TRENCH
(NOTE 9)
SCALE: 1" = 4'

LINER SYSTEM COMPONENT SUMMARY (NOTE 2)		
GEOSYNTHETICS		
COMPONENT	MATERIAL	SPECIFICATION SECTION
PRIMARY GEOMEMBRANE LINER	TEXTURED 80-mil HDPE	02770
SECONDARY GEOMEMBRANE LINER	TEXTURED 80-mil HDPE	02770
PRIMARY GEOSYNTHETIC CLAY LINER	INTERNALLY-REINFORCED SODIUM MONTMORILLONITE CORE WITH WOVEN GEOTEXTILE SIDE AGAINST OVERLYING GEOMEMBRANE AND NONWOVEN SIDE AGAINST UNDERLYING SOIL, OR SODIUM MONTMORILLONITE CORE WITH 40-mil TEXTURED HDPE BACKING AGAINST UNDERLYING SOIL	02772
SECONDARY GEOSYNTHETIC CLAY LINER	INTERNALLY-REINFORCED SODIUM MONTMORILLONITE CORE WITH WOVEN GEOTEXTILE SIDE AGAINST OVERLYING GEOMEMBRANE AND NONWOVEN SIDE AGAINST UNDERLYING SOIL, OR SODIUM MONTMORILLONITE CORE WITH 40-mil TEXTURED HDPE BACKING AGAINST UNDERLYING SOIL	02772
GEOTEXTILE FILTER	POLYPROPYLENE OR POLYESTER NEEDLE-PUNCHED NONWOVEN GEOTEXTILE	02714
GEOTEXTILE CUSHION	POLYPROPYLENE OR POLYESTER NEEDLE-PUNCHED NONWOVEN GEOTEXTILE	02714
SUPPLEMENTAL GEOTEXTILE CUSHION	POLYPROPYLENE OR POLYESTER NEEDLE-PUNCHED NONWOVEN GEOTEXTILE	02714
SOILS		
COMPONENT	SOURCE	SPECIFICATION SECTION
PREPARED SUBGRADE/COMPACTED FILL	ON-SITE BORROW	02200
COMPACTED CLAY LINER	ON-SITE BORROW	02225
LDS DRAINAGE LAYER	OFF-SITE BORROW	02710
LDS DRAINAGE CORRIDOR	OFF-SITE BORROW	02710
LCS DRAINAGE LAYER	OFF-SITE BORROW	02710
LCS DRAINAGE CORRIDOR	OFF-SITE BORROW	02710
PROTECTIVE LAYER (NON-GRANULAR)	ON-SITE IMPACTED MATERIAL OR ON-SITE BORROW	02240
PROTECTIVE LAYER (GRANULAR)	ON-SITE IMPACTED MATERIAL OR OFF-SITE BORROW	02240



15 / - **DETAIL**
LINER SYSTEM WITH LCS AND LDS PIPES
(NOTE 8)
SCALE: 1" = 2'



16 / G-27 **DETAIL**
LINER SYSTEM AT PERIMETER BERM
SCALE: 1" = 4'



17 / G-16 **DETAIL**
LINER SYSTEM AT INTERCELL BERM AND PERIMETER BERM INTERSECTION
SCALE: 1" = 4'



18 / G-28 **DETAIL**
LINER SYSTEM AT PERIMETER BERM AND IMPACTED RUNOFF CATCHMENT AREA
SCALE: 1" = 4'

NOTES:

1. DETAILS ARE SHOWN TO SCALE AS NOTED EXCEPT FOR THE GEOSYNTHETICS WHICH ARE SHOWN AT AN EXAGGERATED SCALE FOR CLARITY. MATERIAL TOLERANCES SHALL BE WITHIN THE LIMITS GIVEN IN THE OSDF SPECIFICATIONS.
2. LINER SYSTEM COMPONENT SUMMARY IS PROVIDED FOR INFORMATION PURPOSES ONLY. THE OSDF SPECIFICATIONS SHALL BE REFERENCED FOR DETAILED MINIMUM REQUIREMENTS FOR EACH MATERIAL.
3. PROTECTIVE LAYER IN ACTIVE CELLS SHALL CONSIST OF IMPACTED OR NON-IMPACTED GRANULAR MATERIAL IN THE IMPACTED RUNOFF CATCHMENT AREA AND IMPACTED NON-GRANULAR MATERIAL IN REMAINING AREAS. PROTECTIVE LAYER SHALL BE IN ACCORDANCE WITH SECTION 02240 OF THE OSDF SPECIFICATIONS.
4. CONSTRUCTION CONTROL POINT TABLES ARE PROVIDED ON DRAWINGS G-38 AND G-39.
5. THICKNESS OF COMPACTED CLAY LINER ALONG CENTERLINE OF INTERCELL BERM VARIES FROM A MINIMUM OF 3 FEET TO A MAXIMUM OF 7 FEET.
6. SACRIFICIAL PROTECTIVE CLAY LAYER SHALL BE OVERBUILT A MINIMUM OF 2 FEET ABOVE TOP OF COMPACTED CLAY CAP ELEVATIONS AND CUT BACK JUST PRIOR TO CONSTRUCTION OF THE FINAL COVER SYSTEM. SACRIFICIAL PROTECTIVE CLAY LAYER SHALL BE IN ACCORDANCE WITH SECTION 02200 OF THE OSDF SPECIFICATIONS.
7. LCS AND LDS PIPES SHALL BE IN ACCORDANCE WITH SECTION 02605 OF THE OSDF SPECIFICATIONS.
8. THIS DETAIL IS CONCEPTUAL TO DEMONSTRATE COMPLIANCE WITH THE FEMP OPERABLE UNIT 2 RECORD OF DECISION.
9. TRENCHING AND BACKFILLING OF LINER SYSTEM ANCHOR TRENCH SHALL BE IN ACCORDANCE WITH SECTION 02215 OF THE OSDF SPECIFICATIONS.

REV. NO.	DATE	DESCRIPTION	DES BY	DR BY	CHK BY	RVW BY	APP BY
G	11.10.96	FINAL SUBMITTAL TO EPA	DLVL	RD	LA	KWC	RB
F	25.06.96	PREFINAL SUBMITTAL TO EPA					

SCALE AS SHOWN

FOR INFORMATION ONLY

OWNER/FACILITY:
UNITED STATES DEPARTMENT OF ENERGY
FERNALD ENVIRONMENTAL MANAGEMENT PROJECT

CLIENT:
FERMCO Fernald Environmental Restoration Management Corporation

PROJECT:
ON-SITE DISPOSAL FACILITY

TITLE:
LINER SYSTEM DETAILS I 468
240017_13

THIS DRAWING MAY NOT BE ISSUED FOR PROJECT TENDER OR CONSTRUCTION, UNLESS SEALED.

Rudolph Bonaparte
SIGNATURE
8 Oct 1996
DATE

STATE OF OHIO
RUDOLPH BONAPARTE
E-56679
REGISTERED PROFESSIONAL ENGINEER

GeoSyntec Consultants
1100 LAKE HEARN DRIVE
ATLANTA, GEORGIA 30342 USA

FERMCO PROJECT NO.:	20100
FERMCO SUBCONTRACT NO.:	95PS005028
FERMCO DRAWING NO.:	90X-6000-00032
GEOSYNTEC PROJECT NO.:	GE3900-13.1
GEOSYNTEC DOCUMENT NO.:	F96-G094
SHEET NO.:	G-22
REVISION NO.:	G

FINAL DESIGN PACKAGE

H:\F96-g094 Wed Oct 09 15:26:11 1996 J MILLER



19 G-29 DETAIL
LINER SYSTEM SEASONAL TERMINATION AT INTERCELL BERM AND IMPACTED RUNOFF CATCHMENT AREA
(NOTE 5)
SCALE: 1" = 4'
XREF: F96H0232



20 G-29 DETAIL
LINER SYSTEM SEASONAL TERMINATION AT INTERCELL BERM
SCALE: 1" = 4'
XREF: F96H0274



21 G-15 DETAIL
LINER SYSTEM AT LEACHATE COLLECTION AND LEAK DETECTION CORRIDOR
(NOTE 5)
SCALE: 1" = 4'
XREF: F96H0295



22 G-23 DETAIL
GEOMEMBRANE RAIN FLAP AT IMPACTED RUNOFF CATCHMENT AREA
SCALE: 1" = 2'
XREF: F96H0360

NOTES:

1. DETAILS ARE SHOWN TO SCALE AS NOTED EXCEPT FOR THE GEOSYNTHETICS WHICH ARE SHOWN AT AN EXAGGERATED SCALE FOR CLARITY. MATERIAL TOLERANCES SHALL BE WITHIN THE LIMITS GIVEN IN THE OSDF SPECIFICATIONS.
2. PROTECTIVE LAYER IN ACTIVE CELLS SHALL CONSIST OF IMPACTED OR NON-IMPACTED GRANULAR MATERIAL IN THE IMPACTED RUNOFF CATCHMENT AREA AND IMPACTED NON-GRANULAR MATERIAL IN REMAINING AREAS. PROTECTIVE LAYER IN FUTURE CELLS SHALL CONSIST OF NON-IMPACTED NON-GRANULAR MATERIAL. PROTECTIVE LAYER SHALL BE IN ACCORDANCE WITH SECTION 02240 OF THE OSDF SPECIFICATIONS.
3. CONSTRUCTION CONTROL POINT TABLES ARE PROVIDED ON DRAWINGS G-38 AND G-39.
4. THICKNESS OF COMPACTED CLAY LINER ALONG CENTERLINE OF INTERCELL BERM VARIES FROM A MINIMUM OF 3 FEET TO A MAXIMUM OF 7 FEET.
5. LCS AND LDS PIPES SHALL BE IN ACCORDANCE WITH SECTION 02605 OF THE OSDF SPECIFICATIONS.
6. TEMPORARY PLASTIC COVER SHALL CONSIST OF 10-mil THICK (MIN) POLYETHYLENE, POLYVINYL CHLORIDE, OR OTHER SHEETING APPROVED BY THE CONSTRUCTION MANAGER. SUBCONTRACTOR SHALL WEIGHT TEMPORARY PLASTIC COVER WITH SANDBAGS, OR EQUIVALENT, TO PREVENT DAMAGE FROM WIND.
7. RAIN FLAP SHALL BE CONTINUOUSLY WELDED TO THE PRIMARY GEOMEMBRANE LINER ALONG THE INTERCELL BERM. FLAP SHALL TIE-IN TO THE GEOMEMBRANE AT THE CREST OF THE PERIMETER BERM AND EXTEND 185 FEET TO THE EAST FROM THE WEST PERIMETER BERM BASELINE.
8. MATERIAL IN DRAINAGE LAYERS AND DRAINAGE CORRIDORS SHALL BE IN ACCORDANCE WITH SECTION 02710 OF THE OSDF SPECIFICATIONS.

REV. NO.	DATE	DESCRIPTION	DES BY	DR BY	CHK BY	RVW BY	APP BY
G	11.10.96	FINAL SUBMITTAL TO EPA	DLVL	RD	LA	KWC	RB
F	25.06.96	PREFINAL SUBMITTAL TO EPA					

SCALE AS SHOWN

FOR INFORMATION ONLY

OWNER/FACILITY:
UNITED STATES DEPARTMENT OF ENERGY
FERNALD ENVIRONMENTAL MANAGEMENT PROJECT

CLIENT:
FERMCO Environmental Restoration Management Corporation
FERNALD ENVIRONMENTAL RESTORATION MANAGEMENT CORPORATION

PROJECT:
ON-SITE DISPOSAL FACILITY

TITLE:
LINER SYSTEM DETAILS II 469
24001214

THIS DRAWING MAY NOT BE ISSUED FOR PROJECT TENDER OR CONSTRUCTION, UNLESS SEALED.

Rudolph Bonaparte
SIGNATURE
8 Oct 1996
DATE

STATE OF OHIO
RUDOLPH BONAPARTE
E-56679
REGISTERED PROFESSIONAL ENGINEER
SEAL

GEO SYNTEC CONSULTANTS
1100 LAKE HEARN DRIVE
ATLANTA, GEORGIA 30342 USA

FERMCO PROJECT NO.:	20100
FERMCO SUBCONTRACT NO.:	95PS005028
FERMCO DRAWING NO.:	90X-6000-G-00033
GEOSYNTEC PROJECT NO.:	GE3900-13.1
GEOSYNTEC DOCUMENT NO.:	F96-0095
SHEET NO.:	G-23
REVISION NO.:	G

FINAL DESIGN PACKAGE

M:\ACAD\GE3900-13\F96-0095 Sat Oct 05 12:12:20 1996 FERNCO/DUAN



23 / G-24 **DETAIL**
LINER SYSTEM GEOSYNTHETICS AT LINER PENETRATION
SCALE: 1" = 1'



A / G-9 **SECTION**
LEACHATE COLLECTION AND LEAK DETECTION CORRIDOR AT CELL OUTLET
SCALE: 1" = 2'



B / G-9 **SECTION**
PENETRATION OF LDS PIPE THROUGH LINER SYSTEM
(NOTE 7)
SCALE: 1" = 2'



24 / G-24 **DETAIL**
PERFORATED PIPE
SCALE: 1" = 6"



C / G-9 **SECTION**
PENETRATION OF REDUNDANT LCS PIPE THROUGH LINER SYSTEM
(NOTE 7)
SCALE: 1" = 2'



D / G-9 **SECTION**
PENETRATION OF LCS PIPE THROUGH LINER SYSTEM
(NOTE 7)
SCALE: 1" = 2'

NOTES:

1. DETAILS ARE SHOWN TO SCALE AS NOTED EXCEPT FOR THE GEOSYNTHETICS WHICH ARE SHOWN AT AN EXAGGERATED SCALE FOR CLARITY. MATERIAL TOLERANCES SHALL BE WITHIN THE LIMITS GIVEN IN THE OSDF SPECIFICATIONS.
2. PROTECTIVE LAYER IN ACTIVE CELLS SHALL CONSIST OF IMPACTED MATERIAL OR NON-IMPACTED GRANULAR MATERIAL IN THE IMPACTED RUNOFF CATCHMENT AREA AND IMPACTED NON-GRANULAR MATERIAL IN REMAINING AREAS. PROTECTIVE LAYER IN FUTURE CELLS SHALL CONSIST OF NON-IMPACTED NON-GRANULAR MATERIAL. PROTECTIVE LAYER SHALL BE IN ACCORDANCE WITH SECTION 02240 OF THE OSDF SPECIFICATIONS.
3. CONSTRUCTION CONTROL POINT TABLES ARE PROVIDED ON DRAWINGS G-38 AND G-39.
4. LCS AND LDS PIPES SHALL BE IN ACCORDANCE WITH SECTION 02605 OF THE OSDF SPECIFICATIONS.
5. LINER PENETRATION BOXES SHALL BE IN ACCORDANCE WITH SECTION 13005 OF THE OSDF SPECIFICATIONS.
6. MATERIAL IN DRAINAGE LAYERS AND DRAINAGE CORRIDORS SHALL BE IN ACCORDANCE WITH SECTION 02710 OF THE OSDF SPECIFICATIONS.
7. HORIZONTAL MONITORING WELL IS NOT SHOWN IN THIS SECTION FOR CLARITY.

REV. NO.	DATE	DESCRIPTION	DES BY	DR BY	CHK BY	RVW BY	APP BY
G	11.10.96	FINAL SUBMITTAL TO EPA	DLVL	BD	LA	KWC	RB
F	25.06.96	PREFINAL SUBMITTAL TO EPA					

SCALE AS SHOWN

FOR INFORMATION ONLY

OWNER/FACILITY:
UNITED STATES DEPARTMENT OF ENERGY
FERNALD ENVIRONMENTAL MANAGEMENT PROJECT

CLIENT:
FERMCO FERNALD ENVIRONMENTAL RESTORATION MANAGEMENT CORPORATION

PROJECT:
ON-SITE DISPOSAL FACILITY

TITLE:
LINER SYSTEM DETAILS III 470
240017_15

THIS DRAWING MAY NOT BE ISSUED FOR PROJECT TENDER OR CONSTRUCTION, UNLESS SEALED.

Rudolph Bonaparte
SIGNATURE
8 Oct 1996
DATE

STATE OF OHIO
RUDOLPH BONAPARTE
E-56679
REGISTERED PROFESSIONAL ENGINEER

GEO SYNTEC CONSULTANTS
1100 LAKE HEARN DRIVE
ATLANTA, GEORGIA 30342 USA

FERMCO PROJECT NO.:	20100
FERMCO SUBCONTRACT NO.:	95P5005028
FERMCO DRAWING NO.:	90X-6000-G-00034
GEOSYNTEC PROJECT NO.:	GE3900-13.1
GEOSYNTEC DOCUMENT NO.:	F96-G029
SHEET NO.:	G-24
REVISION NO.:	G

FINAL DESIGN PACKAGE

M:\GAZADOC\GE3900-13\F96-G029 Sat Oct 05 09:29:42 1996 John C.



PLAN VIEW



ISOMETRIC



FRONT ELEVATION



RIGHT ELEVATION

25 G-24 DETAIL
LINER PENETRATION BOX TYPE I
SCALE: 1" = 1'



PLAN VIEW



ISOMETRIC



FRONT ELEVATION



RIGHT ELEVATION

26 G-24 DETAIL
LINER PENETRATION BOX TYPE II
SCALE: 1" = 1'



PLAN VIEW



ISOMETRIC



FRONT ELEVATION



RIGHT ELEVATION

27 G-24 DETAIL
LINER PENETRATION BOX TYPE III
SCALE: 1" = 1'



PLAN VIEW



ISOMETRIC



FRONT ELEVATION



RIGHT ELEVATION

28 G-24 DETAIL
LINER PENETRATION BOX TYPE IV
SCALE: 1" = 1'

FOR INFORMATION ONLY

NOTES:

1. LINER PENETRATION BOXES SHALL BE IN ACCORDANCE WITH SECTION 13005 OF THE OSDF SPECIFICATIONS.
2. PIPES ARE NOT SHOWN FOR CLARITY. SEE DRAWING G-24 FOR LENGTH OF PIPES
3. LINER PENETRATION BOXES SHALL BE CONSTRUCTED USING 1-INCH THICK HDPE FLAT STOCK.
4. LINER PENETRATION BOXES SHALL BE AIR PRESSURE TESTED IN THE FIELD AFTER INSTALLATION. AIR PRESSURE TEST CHAMBER SHALL BE BACKFILLED WITH BENTONITE POWDER AFTER AIR PRESSURE TESTING AND SEAMING OF GEOMEMBRANE TO LINER PENETRATION BOXES IS COMPLETED. PLUG SHALL BE SEALED WITH HDPE EXTRUDATE AFTER BACKFILLING WITH BENTONITE POWDER.

FINAL DESIGN PACKAGE

REV. NO.	DATE	DESCRIPTION	DES BY	DR BY	CHK BY	RVW BY	APP BY
G	11.10.96	FINAL SUBMITTAL TO EPA	DLVL	UMW	LA	KWC	RB
F	25.06.96	PREFINAL SUBMITTAL TO EPA					

1 5 0 1 2
SCALE IN FEET

OWNER/FACILITY:
UNITED STATES DEPARTMENT OF ENERGY
FERNALD ENVIRONMENTAL MANAGEMENT PROJECT

CLIENT:
FERMCO Fernald Environmental Restoration Management Corporation
FERNALD ENVIRONMENTAL RESTORATION MANAGEMENT CORPORATION

PROJECT:
ON-SITE DISPOSAL FACILITY

TITLE:
LINER SYSTEM DETAILS IV 471
24D017-16

THIS DRAWING MAY NOT BE ISSUED FOR PROJECT TENDER OR CONSTRUCTION, UNLESS SEALED.

Rudolph Bonaparte
SIGNATURE
5 Oct 1996
DATE

STATE OF OHIO
RUDOLPH BONAPARTE
E-56679
REGISTERED PROFESSIONAL ENGINEER
SEAL

GeoSyntec Consultants
1100 LAKE HEARN DRIVE
ATLANTA, GEORGIA 30342 USA

FERMCO PROJECT NO.:	20100
FERMCO SUBCONTRACT NO.:	95PS005028
FERMCO DRAWING NO.:	90X-6000-G-00035
GEOSYNTEC PROJECT NO.:	GE3900-13.1
GEOSYNTEC DOCUMENT NO.:	F96-G113
SHEET NO.:	G-25
REVISION NO.:	G

H:\96-g113 Tue Oct 08 09:35:18 1996 J.MILLER



29 G-20 **DETAIL**
FINAL COVER SYSTEM AND LINER SYSTEM TIE-IN
SCALE: 1" = 4'
IREF: F96I0220



30 G-29 **DETAIL**
FINAL COVER SYSTEM WITH SEASONAL CLOSURE
SCALE: 1" = 4'
IREF: F96I0078



31 G-15 **DETAIL**
FINAL COVER SYSTEM
SCALE: 1" = 2'
IREF: F96I0229

COVER SYSTEM COMPONENT SUMMARY (NOTE 2)		
GEOSYNTHETICS		
COMPONENT	MATERIAL	SPECIFICATION SECTION
GEOMEMBRANE CAP	TEXTURED 60-mil HDPE	02770
GEOSYNTHETIC CLAY CAP	INTERNALLY-REINFORCED SODIUM MONTMORILLONITE CORE WITH WOVEN GEOTEXTILE SIDE AGAINST OVERLYING GEOMEMBRANE AND NONWOVEN SIDE AGAINST UNDERLYING SOIL; OR SODIUM MONTMORILLONITE CORE WITH 40-mil TEXTURED HDPE BACKING AGAINST UNDERLYING SOIL	02772
GEOTEXTILE CUSHION	POLYPROPYLENE OR POLYESTER NEEDLE-PUNCHED NONWOVEN GEOTEXTILE	02714
SOILS		
COMPONENT	SOURCE	SPECIFICATION SECTION
COMPACTED CLAY CAP	ON-SITE BORROW	02225
COVER DRAINAGE LAYER	OFF-SITE BORROW	02710
BIOINTRUSION BARRIER	OFF-SITE BORROW	02280
GRANULAR FILTER	OFF-SITE BORROW	02712
VEGETATIVE SOIL LAYER	ON-SITE BORROW	02250
TOPSOIL	ON-SITE OR OFF-SITE BORROW	02920
PROTECTIVE LAYER (GRANULAR)	OFF-SITE BORROW	02240

NOTES:

1. DETAILS ARE SHOWN TO SCALE AS NOTED EXCEPT FOR THE GEOSYNTHETICS WHICH ARE SHOWN AT AN EXAGGERATED SCALE FOR CLARITY. MATERIAL TOLERANCES SHALL BE WITHIN THE LIMITS GIVEN IN THE OSDF SPECIFICATIONS.
2. COVER SYSTEM COMPONENT SUMMARY IS PROVIDED FOR INFORMATION PURPOSES ONLY. THE OSDF SPECIFICATIONS SHALL BE REFERENCED FOR DETAILED MINIMUM REQUIREMENTS FOR EACH MATERIAL.
3. CONSTRUCTION CONTROL POINT TABLES WILL BE PROVIDED ON DRAWINGS G-38 AND G-39.
4. A MINIMUM THICKNESS OF 3 FEET OF SELECT IMPACTED MATERIAL SHALL BE PLACED ABOVE THE PROTECTIVE LAYER AND BELOW THE CONTOURING LAYER. THIS THICKNESS MAY BE REDUCED TO 2 FEET ABOVE THE PROTECTIVE LAYER IF THE FIRST LIFT OF IMPACTED MATERIAL PLACEMENT IS CATEGORY 1 OR 2 MATERIAL AS DEFINED BY THE OSDF IMPACTED MATERIAL PLACEMENT (IMP) PLAN. ALL IMPACTED MATERIAL SHALL BE PLACED IN ACCORDANCE WITH SECTION 13010 OF THE OSDF SPECIFICATIONS AND THE IMP PLAN.
5. A GRAVEL CHOKE LAYER SHALL BE COMPACTED INTO THE TOP 6 INCHES OF THE BIOINTRUSION BARRIER IN ACCORDANCE WITH SECTION 02280 OF THE OSDF SPECIFICATIONS.
6. CONTOURING LAYER SHALL CONSIST OF NON-GRANULAR IMPACTED MATERIAL IN ACCORDANCE WITH SECTION 02240 OF THE OSDF SPECIFICATIONS.
7. SEASONAL COVER SOIL SHALL BE IN ACCORDANCE WITH SECTION 13030 OF THE OSDF SPECIFICATIONS.
8. PROTECTIVE LAYER IN ACTIVE CELLS SHALL CONSIST OF IMPACTED OR NON-IMPACTED GRANULAR MATERIAL IN THE IMPACTED RUNOFF CATCHMENT AREA AND IMPACTED NON-GRANULAR MATERIAL IN REMAINING AREAS. PROTECTIVE LAYER AT FINAL COVER SYSTEM WITH SEASONAL CLOSURE SHALL BE NON-IMPACTED NON-GRANULAR MATERIAL. PROTECTIVE LAYER SHALL BE IN ACCORDANCE WITH SECTION 02240 OF THE OSDF SPECIFICATIONS.
9. TEMPORARY EROSION MAT SHALL BE IN ACCORDANCE WITH SECTION 02270 OF THE OSDF SPECIFICATIONS.
10. THE SLOPE OF THE LOWER PORTION OF THE FINAL COVER SYSTEM IS 6H:1V FOR THE NORTH, SOUTH, EAST, AND WEST PERIMETERS OF THE OSDF AND TRANSITIONS FROM 6H:1V TO 7H:1V AND BACK TO 6H:1V IN THE CORNERS OF THE OSDF.

REV. NO.	DATE	DESCRIPTION	DES BY	DR BY	CHK BY	RVW BY	APP BY
G	11.10.96	FINAL SUBMITTAL TO EPA	DLVL	UMW	LA	KWC	RB
F	25.06.96	PREFINAL SUBMITTAL TO EPA					

SCALE AS SHOWN

FOR INFORMATION ONLY

OWNER/FACILITY:
UNITED STATES DEPARTMENT OF ENERGY
FERNALD ENVIRONMENTAL MANAGEMENT PROJECT

CLIENT:
FERNALD ENVIRONMENTAL RESTORATION MANAGEMENT CORPORATION

PROJECT:
ON-SITE DISPOSAL FACILITY

TITLE:
COVER SYSTEM DETAILS I 472
240017_16

THIS DRAWING MAY NOT BE ISSUED FOR PROJECT TENDER OR CONSTRUCTION, UNLESS SEALED.

STATE OF OHIO · RUDOLPH BONAPARTE · E-56579 · REGISTERED PROFESSIONAL ENGINEER

Rudolph Bonaparte
SIGNATURE
8 Oct 1996
DATE

GeoSyntec Consultants
1100 LAKE HEARN DRIVE
ATLANTA, GEORGIA 30342 USA

FERMCO PROJECT NO.:	20100
FERMCO SUBCONTRACT NO.:	95PS005028
FERMCO DRAWING NO.:	90X-6000-G-00036
GEOSYNTEC PROJECT NO.:	GE3900-13.1
GEOSYNTEC DOCUMENT NO.:	F96-G098
SHEET NO.:	G-26
REVISION NO.:	G

FINAL DESIGN PACKAGE

M:\CAD\ODC\GE3900 - 13\F96-G098 Sat Oct 05 09:53:17 1996 John C.

452



SECTION
WEST-EAST SEASONAL CLOSURE

HORIZONTAL SCALE: 1" = 30'
VERTICAL SCALE: 1" = 10'
XREF: F96A0330



32 G-27 DETAIL
WEST PERIMETER WITH IMPACTED MATERIAL HAUL ROAD AND SEASONAL CLOSURE

(NOTE 10)
SCALE: 1" = 4'
XREF: F96A0346



33 G-27 DETAIL
EAST PERIMETER WITH SEASONAL CLOSURE

(NOTE 10)
SCALE: 1" = 4'
XREF: F96A0255

NOTES:

1. EXISTING GROUND ELEVATIONS BASED ON 1992 SITE FLYOVER.
2. ELEVATIONS ARE IN FEET ABOVE SEA LEVEL DATUM. (NOTE: "SEA LEVEL DATUM" REFERS TO THE NATIONAL GEODETIC VERTICAL DATUM [NGVD].)
3. DETAILS ARE SHOWN TO SCALE AS NOTED EXCEPT FOR THE GEOSYNTHETICS WHICH ARE SHOWN AT AN EXAGGERATED SCALE FOR CLARITY. MATERIAL TOLERANCES SHALL BE WITHIN THE LIMITS GIVEN IN THE OSDF SPECIFICATIONS.
4. SACRIFICIAL PROTECTIVE CLAY LAYER SHALL BE CONSTRUCTED A MINIMUM OF 2 FEET ABOVE TOP OF COMPACTED CLAY CAP ELEVATIONS AND CUT BACK JUST PRIOR TO CONSTRUCTION OF THE FINAL COVER SYSTEM. SACRIFICIAL PROTECTIVE CLAY LAYER SHALL BE IN ACCORDANCE WITH SECTION 02200 OF THE OSDF SPECIFICATIONS.
5. CONSTRUCTION CONTROL POINT TABLES ARE PROVIDED ON DRAWINGS G-38 AND G-39.
6. A MINIMUM THICKNESS OF 3 FEET OF SELECT IMPACTED MATERIAL SHALL BE PLACED ABOVE THE PROTECTIVE LAYER AND BELOW THE CONTOURING LAYER. THIS THICKNESS MAY BE REDUCED TO 2 FEET ABOVE THE PROTECTIVE LAYER IF THE FIRST LIFT OF IMPACTED MATERIAL PLACEMENT IS CATEGORY 1 OR 2 MATERIAL AS DEFINED BY THE OSDF IMPACTED MATERIAL PLACEMENT (IMP) PLAN. ALL IMPACTED MATERIAL SHALL BE PLACED IN ACCORDANCE WITH SECTION 13010 OF THE OSDF SPECIFICATIONS AND THE IMP PLAN.
7. CONTOURING LAYER SHALL CONSIST OF NON-GRANULAR IMPACTED MATERIAL IN ACCORDANCE WITH SECTION 02240 OF THE OSDF SPECIFICATIONS.
8. PROTECTIVE LAYER IN ACTIVE CELLS SHALL CONSIST OF IMPACTED OR NON-IMPACTED GRANULAR MATERIAL IN THE IMPACTED RUNOFF CATCHMENT AREA AND IMPACTED NON-GRANULAR MATERIAL IN REMAINING AREAS. PROTECTIVE LAYER SHALL BE IN ACCORDANCE WITH SECTION 02240 OF THE OSDF SPECIFICATIONS.
9. SUBCONTRACTOR SHALL ESTABLISH ACCESS TO CELL LINER SYSTEM CONSTRUCTION, FINAL COVER SYSTEM CONSTRUCTION, AND IMPACTED MATERIAL PLACEMENT IN ACCORDANCE WITH THE APPROVED CONSTRUCTION SITE ACCESS PLAN.

FINAL DESIGN PACKAGE

FOR INFORMATION ONLY

REV. NO.	DATE	DESCRIPTION	DES BY	DR BY	CHK BY	RVW BY	APP BY
G	11.10.96	FINAL SUBMITTAL TO EPA	DLVL	RD	LA	KWC	RB
F	25.06.96	PREFINAL SUBMITTAL TO EPA					

SCALE AS SHOWN

OWNER/FACILITY:
UNITED STATES DEPARTMENT OF ENERGY
FERNALD ENVIRONMENTAL MANAGEMENT PROJECT

CLIENT:
FERMCO FERNALD ENVIRONMENTAL RESTORATION MANAGEMENT CORPORATION

PROJECT:
ON-SITE DISPOSAL FACILITY

TITLE:
COVER SYSTEM DETAILS II 473
24017_18

THIS DRAWING MAY NOT BE ISSUED FOR PROJECT TENDER OR CONSTRUCTION, UNLESS SEALED.

STATE OF OHIO — RUDOLPH BONAPARTE — E-56679 — REGISTERED PROFESSIONAL ENGINEER

Rudolph Bonaparte
SIGNATURE
8 Oct 1996
DATE

GeoSyntec Consultants
1100 LAKE HEARN DRIVE
ATLANTA, GEORGIA 30342 USA

FERMCO PROJECT NO.:	20100
FERMCO SUBCONTRACT NO.:	95PS005028
FERMCO DRAWING NO.:	90X-6000-G-00037
GEOSYNTEC PROJECT NO.:	GE3900-13.1
GEOSYNTEC DOCUMENT NO.:	F96-G133
SHEET NO.:	G-27
REVISION NO.:	G

M:\VACADDE\GE3900\F-13\96-G133 Tue Oct 08 09:14:45 1996 John C.

452



SECTION
WEST–EAST SEASONAL CLOSURE AT IMPACTED RUNOFF CATCHMENT AREA

HORIZONTAL SCALE: 1" = 30'
VERTICAL SCALE: 1" = 10'



34 - DETAIL
IMPACTED MATERIAL HAUL ROAD AT PERIMETER BERM

SCALE: 1" = 4'



35 G-28 DETAIL
WEST PERIMETER WITH SEASONAL CLOSURE AND IMPACTED RUNOFF CATCHMENT AREA

SCALE: 1" = 4'

NOTES:

1. EXISTING GROUND ELEVATIONS BASED ON 1992 SITE FLYOVER.
2. ELEVATIONS ARE IN FEET ABOVE SEA LEVEL DATUM. (NOTE: "SEA LEVEL DATUM" REFERS TO THE NATIONAL GEODETIC VERTICAL DATUM [NGVD].)
3. DETAILS ARE SHOWN TO SCALE AS NOTED EXCEPT FOR THE GEOSYNTHETICS WHICH ARE SHOWN AT AN EXAGGERATED SCALE FOR CLARITY. MATERIAL TOLERANCES SHALL BE WITHIN THE LIMITS GIVEN IN THE OSDF SPECIFICATIONS.
4. SACRIFICIAL PROTECTIVE CLAY LAYER SHALL BE CONSTRUCTED A MINIMUM OF 2 FEET ABOVE TOP OF COMPACTED CLAY CAP ELEVATIONS AND CUT BACK JUST PRIOR TO CONSTRUCTION OF THE FINAL COVER SYSTEM. SACRIFICIAL PROTECTIVE CLAY LAYER SHALL BE IN ACCORDANCE WITH SECTION 02200 OF THE OSDF SPECIFICATIONS.
5. CONSTRUCTION CONTROL POINT TABLES ARE PROVIDED ON DRAWINGS G-38 AND G-39.
6. A MINIMUM THICKNESS OF 3 FEET OF SELECT IMPACTED MATERIAL SHALL BE PLACED ABOVE THE PROTECTIVE LAYER AND BELOW THE CONTOURING LAYER. THIS THICKNESS MAY BE REDUCED TO 2 FEET ABOVE THE PROTECTIVE LAYER IF THE FIRST LIFT OF IMPACTED MATERIAL PLACEMENT IS CATEGORY 1 OR 2 MATERIAL AS DEFINED BY THE OSDF IMPACTED MATERIAL PLACEMENT (IMP) PLAN. ALL IMPACTED MATERIAL SHALL BE PLACED IN ACCORDANCE WITH SECTION 13010 OF THE OSDF SPECIFICATIONS AND THE IMP PLAN.
7. PROTECTIVE LAYER IN ACTIVE CELLS SHALL CONSIST OF IMPACTED OR NON-IMPACTED GRANULAR MATERIAL IN THE IMPACTED RUNOFF CATCHMENT AREA AND IMPACTED NON-GRANULAR MATERIAL IN REMAINING AREAS. PROTECTIVE LAYER SHALL BE IN ACCORDANCE WITH SECTION 02240 OF OSDF SPECIFICATIONS.
8. SEASONAL COVER SOIL SHALL BE IN ACCORDANCE WITH SECTION 13030 OF THE OSDF SPECIFICATIONS.
9. SUBCONTRACTOR SHALL ESTABLISH ACCESS TO CELL LINER SYSTEM CONSTRUCTION, FINAL COVER SYSTEM CONSTRUCTION, AND IMPACTED MATERIAL PLACEMENT IN ACCORDANCE WITH THE APPROVED CONSTRUCTION SITE ACCESS PLAN.
10. MATERIAL IN DRAINAGE LAYERS AND DRAINAGE CORRIDORS SHALL BE IN ACCORDANCE WITH SECTION 02710 OF THE OSDF SPECIFICATIONS.

FOR INFORMATION ONLY

REV. NO.	DATE	DESCRIPTION	DES BY	DR BY	CHK BY	RVW BY	APP BY
G	11.10.96	FINAL SUBMITTAL TO EPA	DLVL	JRM	LA	KWC	RB
F	25.06.96	PREFINAL SUBMITTAL TO EPA					

SCALE AS SHOWN

OWNER/FACILITY:
UNITED STATES DEPARTMENT OF ENERGY
FERNALD ENVIRONMENTAL MANAGEMENT PROJECT

CLIENT:

FERNCO Fernald Environmental Restoration Management Corporation

PROJECT:
ON-SITE DISPOSAL FACILITY

TITLE:
COVER SYSTEM DETAILS III 474
24017_19

THIS DRAWING MAY NOT BE ISSUED FOR PROJECT TENDER OR CONSTRUCTION, UNLESS SEALED.

Rudolph Bonaparte
SIGNATURE
8 Oct 1996
DATE

STATE OF OHIO
RUDOLPH BONAPARTE
E-56679
REGISTERED PROFESSIONAL ENGINEER

GeoSyntec Consultants
1100 LAKE HEARN DRIVE
ATLANTA, GEORGIA 30342 USA

FERMCO PROJECT NO.:	20100
FERMCO SUBCONTRACT NO.:	95PS005028
FERMCO DRAWING NO.:	90X-6000-G-00038
GEOSYNTEC PROJECT NO.:	GE3900-13.1
GEOSYNTEC DOCUMENT NO.:	F96-G135
SHEET NO.:	G-28
REVISION NO.:	G

FINAL DESIGN PACKAGE

M:\GAC\ADD\GE3900-13\96-6135 Tue Oct 08 09:04:49 1996 John C.

452



SECTION
NORTH-SOUTH SEASONAL CLOSURE

HORIZONTAL SCALE: 1" = 30'
VERTICAL SCALE: 1" = 10'



SECTION
NORTH-SOUTH SEASONAL CLOSURE AT IMPACTED RUNOFF CATCHMENT AREA

HORIZONTAL SCALE: 1" = 30'
VERTICAL SCALE: 1" = 10'



36 G-29 **DETAIL**
SEASONAL CLOSURE AT INTERCELL BERM

SCALE: 1" = 4'



37 G-29 **DETAIL**
SEASONAL CLOSURE AT INTERCELL BERM AND IMPACTED RUNOFF CATCHMENT AREA

SCALE: 1" = 4'

NOTES:

1. EXISTING GROUND ELEVATIONS BASED ON 1992 SITE FLYOVER.
2. ELEVATIONS ARE IN FEET ABOVE SEA LEVEL DATUM. (NOTE: "SEA LEVEL DATUM" REFERS TO THE NATIONAL GEODETIC VERTICAL DATUM [NGVD].)
3. DETAILS ARE SHOWN TO SCALE AS NOTED EXCEPT FOR THE GEOSYNTHETICS WHICH ARE SHOWN AT AN EXAGGERATED SCALE FOR CLARITY. MATERIAL TOLERANCES SHALL BE WITHIN THE LIMITS GIVEN IN THE OSDF SPECIFICATIONS.
4. A MINIMUM THICKNESS OF 3 FEET OF SELECT IMPACTED MATERIAL SHALL BE PLACED ABOVE THE PROTECTIVE LAYER AND BELOW THE CONTOURING LAYER. THIS THICKNESS MAY BE REDUCED TO 2 FEET ABOVE THE PROTECTIVE LAYER IF THE FIRST LIFT OF IMPACTED MATERIAL PLACEMENT IS CATEGORY 1 OR 2 MATERIAL AS DEFINED BY THE OSDF IMPACTED MATERIAL PLACEMENT (IMP) PLAN. ALL IMPACTED MATERIAL SHALL BE PLACED IN ACCORDANCE WITH SECTION 13010 OF THE OSDF SPECIFICATIONS AND THE IMP PLAN.
5. CONSTRUCTION CONTROL POINT TABLES ARE PROVIDED ON DRAWINGS G-38 AND G-39.
6. SEASONAL COVER SOIL SHALL BE IN ACCORDANCE WITH SECTION 13030 OF THE OSDF SPECIFICATIONS.
7. LCS AND LDS PIPES SHALL BE IN ACCORDANCE WITH SECTION 02605 OF THE OSDF SPECIFICATIONS.
8. TEMPORARY PLASTIC COVER SHALL CONSIST OF 10-mil THICK (MIN) POLYETHYLENE, POLYVINYL CHLORIDE MATERIAL, OR OTHER SHEETING ACCEPTABLE TO THE CONSTRUCTION MANAGER. SUBCONTRACTOR SHALL WEIGHT TEMPORARY PLASTIC COVER WITH SANDBAGS, OR EQUIVALENT, TO PREVENT DAMAGE FROM WIND.
9. RAIN FLAP SHALL BE HDPE AND CONTINUOUSLY WELDED TO THE PRIMARY GEOMEMBRANE LINER ALONG THE INTERCELL BERM. FLAP SHALL TIE-IN TO THE GEOMEMBRANE AT THE CREST OF THE PERIMETER BERM AND EXTEND 185 FEET TO THE EAST FROM THE WEST PERIMETER BERM BASELINE.
10. PROTECTIVE LAYER IN ACTIVE CELLS SHALL CONSIST OF IMPACTED OR NON-IMPACTED GRANULAR MATERIAL IN THE IMPACTED RUNOFF CATCHMENT AREA AND IMPACTED NON-GRANULAR MATERIAL IN REMAINING AREAS. PROTECTIVE LAYER IN FUTURE CELLS SHALL CONSIST OF NON-IMPACTED NON-GRANULAR MATERIAL. PROTECTIVE LAYER SHALL BE IN ACCORDANCE WITH SECTION 02240 OF THE OSDF SPECIFICATIONS.
11. SUBCONTRACTOR SHALL ESTABLISH ACCESS TO CELL LINER SYSTEM CONSTRUCTION, FINAL COVER SYSTEM CONSTRUCTION, AND IMPACTED MATERIAL PLACEMENT IN ACCORDANCE WITH THE APPROVED CONSTRUCTION SITE ACCESS PLAN.

FOR INFORMATION ONLY

REV. NO.	DATE	DESCRIPTION	DES. BY	DR. BY	CHK. BY	RVW. BY	APP. BY
G	11.10.96	FINAL SUBMITTAL TO EPA	DLVL	RD	LA	KWC	RB
F	25.06.96	PREFINAL SUBMITTAL TO EPA					

SCALE AS SHOWN

OWNER/FACILITY:
UNITED STATES DEPARTMENT OF ENERGY
FERNALD ENVIRONMENTAL MANAGEMENT PROJECT

CLIENT:
FERMCO FERNALD ENVIRONMENTAL RESTORATION MANAGEMENT CORPORATION

PROJECT:
ON-SITE DISPOSAL FACILITY

TITLE:
COVER SYSTEM DETAILS IV
240017_20

475

THIS DRAWING MAY NOT BE ISSUED FOR PROJECT TENDER OR CONSTRUCTION, UNLESS SEALED.

Rudolph Bonaparte
SIGNATURE
8 Oct 1996
DATE

STATE OF OHIO
RUDOLPH BONAPARTE
E-56579
REGISTERED PROFESSIONAL ENGINEER

GeoSyntec Consultants
1100 LAKE HEARN DRIVE
ATLANTA, GEORGIA 30342 USA

FERMCO PROJECT NO.:	20100
FERMCO SUBCONTRACT NO.:	95PS005028
FERMCO DRAWING NO.:	90X-6000-G-00039
GEOSYNTEC PROJECT NO.:	GE3900-13.1
GEOSYNTEC DOCUMENT NO.:	F96-G136
SHEET NO.:	G-29
REVISION NO.:	G

FINAL DESIGN PACKAGE

M:\GAC\ADD\GE3900-13\F96-6136 Sat Oct 05 11:29:28 1996 FERMCO/DUNN

452



38 / G-20 DETAIL
NORTH DRAINAGE CHANNEL
SCALE: 1" = 4'
XREF: F96HS293



39 / - DETAIL
NORTH RUN-ON DIVERSION CHANNEL AND BERM
SCALE: 1" = 4'
XREF: F96HS295



40 / G-21 DETAIL
EAST DRAINAGE CHANNEL AND REROUTED NORTH ENTRANCE ROAD
SCALE: 1" = 4' (NOTE 1)
XREF: F96HS304



41 / G-21 DETAIL
WEST DRAINAGE CHANNELS AND ACCESS CORRIDOR
SCALE: 1" = 4' (NOTE 1)
XREF: F96HS294



42 / G-20 DETAIL
SOUTH DRAINAGE CHANNEL
SCALE: 1" = 4'
XREF: F96HS296

NOTES:

1. DETAILS ARE SHOWN TO SCALE AS NOTED EXCEPT FOR THE GEOSYNTHETICS WHICH ARE SHOWN AT AN EXAGGERATED SCALE FOR CLARITY. MATERIAL TOLERANCES SHALL BE WITHIN THE LIMITS GIVEN IN THE OSDF SPECIFICATIONS.
2. CONSTRUCTION CONTROL POINT TABLES ARE PROVIDED ON DRAWINGS G-38 AND G-39.
3. SECTION OF REROUTED NORTH ENTRANCE ROAD OBTAINED FROM DRAWING G0004, "CIVIL TYPICAL SECTION", OF THE "REROUTED NORTH ENTRANCE ROAD CONSTRUCTION DRAWINGS, OPERABLE UNIT 2, PROJECT ORDER 158, REVISION D", PARSONS, APRIL 1996.
4. TEMPORARY EROSION MAT SHALL MEET THE REQUIREMENTS OF SECTION 02270 OF THE OSDF SPECIFICATIONS.

FINAL DESIGN PACKAGE

FOR INFORMATION ONLY

REV. NO.	DATE	DESCRIPTION	DES BY	DR BY	CHK BY	RVW BY	APP BY
F	25.06.96	PREFINAL SUBMITTAL TO EPA					

SCALE AS SHOWN

OWNER/FACILITY:
UNITED STATES DEPARTMENT OF ENERGY
FERNALD ENVIRONMENTAL MANAGEMENT PROJECT

CLIENT:
FERMCO FERNALD ENVIRONMENTAL RESTORATION MANAGEMENT CORPORATION

PROJECT:
ON-SITE DISPOSAL FACILITY 476

TITLE:
STORMWATER MANAGEMENT SYSTEM DETAILS I

24007-21

THIS DRAWING MAY NOT BE ISSUED FOR PROJECT TENDER OR CONSTRUCTION, UNLESS SEALED.

STATE OF OHIO — RUDOLPH BONAPARTE — E-56679 — REGISTERED PROFESSIONAL ENGINEER

Rudolph Bonaparte
SIGNATURE
8 Oct 1996
DATE

GeoSyntec Consultants
1100 LAKE HEARN DRIVE
ATLANTA, GEORGIA 30342 USA

FERMCO PROJECT NO.:	20100
FERMCO SUBCONTRACT NO.:	95PS005028
FERMCO DRAWING NO.:	90X-6000-G-00040
GEOSYNTEC PROJECT NO.:	GE3900-13.1
GEOSYNTEC DOCUMENT NO.:	F96-G118
SHEET NO.:	G-30
REVISION NO.:	G

M:\GACADD\GE3900\-13\F96-G118 Sat Oct 05 09:56:54 1996 John C.



43 G-7 PLAN
DRAINAGE CHANNEL GRAVITY INLET STRUCTURE AND CULVERT
SCALE: 1" = 2'
XREF: F96IG463



D G-31 SECTION
DRAINAGE CHANNEL GRAVITY INLET CULVERT
SCALE: NTS
XREF: F96IG386





B G-31 SECTION
DRAINAGE CHANNEL GRAVITY INLET STRUCTURE
SCALE: 1" = 2'
XREF: F96IG385



A G-31 SECTION
DRAINAGE CHANNEL GRAVITY INLET STRUCTURE
(NOTE 1)
SCALE: 1" = 2' (NOTE 1)
XREF: F96IG464



C G-31 SECTION
DRAINAGE CHANNEL GRAVITY INLET STRUCTURE AND CULVERT
(NOTE 8)
SCALE: 1" = 1'
XREF: F96IG386

NOTES:

1. DETAILS ARE SHOWN TO SCALE AS NOTED EXCEPT FOR THE GEOSYNTHETICS, WHICH ARE SHOWN AT AN EXAGGERATED SCALE FOR CLARITY. MATERIAL TOLERANCES SHALL BE WITHIN THE LIMITS GIVEN IN THE OSDF SPECIFICATIONS.
2. GRAVITY DRAINAGE INLET STRUCTURES SHALL BE IN ACCORDANCE WITH SECTION 03100 OF THE OSDF SPECIFICATIONS
3. REINFORCED CONCRETE PIPE CULVERTS AND JOINTS SHALL BE IN ACCORDANCE WITH SECTION 02721 OF THE OSDF SPECIFICATIONS.
4. TRENCHING AND BACKFILLING SHALL BE IN ACCORDANCE WITH SECTION 02215 OF THE OSDF SPECIFICATIONS.
5. ANTI-VORTEX SUPPORTS DO NOT APPEAR IN ALL SECTIONS. SEE PLAN ON THIS SHEET FOR LOCATIONS.
6. DRAINAGE CHANNEL SLOPE OF 0.75 PERCENT IS TYPICAL FOR CELLS 1 THROUGH 6 AND DRAINAGE CHANNEL SLOPE OF 0.50 PERCENT IS TYPICAL FOR CELLS 7 THROUGH 9.
7. MANHOLE COVER SLAB, MANHOLE EMBEDMENT FILL AND 25-YEAR DRAINAGE CHANNEL SHOWN FOR CLARITY. LEACHATE COLLECTION SYSTEM AND LEACHATE DETECTION SYSTEM MANHOLES ARE NOT SHOWN IN THIS SECTION.
8. RIPRAP TYPE D IS NOT SHOWN IN THIS SECTION.
9. CONSTRUCTION CONTROL POINT TABLES ARE PROVIDED ON DRAWING G-38. THE "*" SYMBOL REPRESENTS THE CELL AT WHICH THE APPROPRIATE GRAVITY DRAINAGE INLET STRUCTURES ARE LOCATED. ONE GRAVITY DRAINAGE INLET STRUCTURE IS LOCATED ADJACENT TO EACH MANHOLE COVER SLAB AND ONE GRAVITY DRAINAGE INLET STRUCTURE IS LOCATED AT THE CENTER LINE OF THE INTERCELL BERM. THERE WILL BE EIGHT GRAVITY DRAINAGE INLET STRUCTURE CONSTRUCTION CONTROL POINTS PER CELL, EXCEPT FOR CELL NO. 9 WHICH HAS 4 CONSTRUCTION CONTROL POINTS.

REV. NO.	DATE	DESCRIPTION	DES. BY	DR. BY	CHK. BY	RVW. BY	APP. BY
G	11.10.96	FINAL SUBMITTAL TO EPA	PR	RD	DLVL	KWC	RB
F	25.06.96	PREFINAL SUBMITTAL TO EPA					

SCALE AS SHOWN

FOR INFORMATION ONLY

OWNER/FACILITY:
UNITED STATES DEPARTMENT OF ENERGY
FERNALD ENVIRONMENTAL MANAGEMENT PROJECT

CLIENT:
FERMCO FERNALD ENVIRONMENTAL RESTORATION MANAGEMENT CORPORATION

PROJECT:
ON-SITE DISPOSAL FACILITY 477

TITLE:
STORMWATER MANAGEMENT SYSTEM DETAILS II
240017_22

THIS DRAWING MAY NOT BE ISSUED FOR PROJECT TENDER OR CONSTRUCTION, UNLESS SEALED.

STATE OF OHIO RUDOLPH BONAPARTE E-56879 REGISTERED PROFESSIONAL ENGINEER

Rudolph Bonaparte SIGNATURE
8 Oct 1996 DATE

GeoSyntec Consultants
1100 LAKE HEARN DRIVE ATLANTA, GEORGIA 30342 USA

FERMCO PROJECT NO.:	20100
FERMCO SUBCONTRACT NO.:	95PS005028
FERMCO DRAWING NO.:	90X-6000-G-00041
GEOSYNTEC PROJECT NO.:	GE3900-13.1
GEOSYNTEC DOCUMENT NO.:	F96-G142
SHEET NO.:	G-31
REVISION NO.:	G

FINAL DESIGN PACKAGE

H:\F96-6142 Wed Oct 09 12:07:50 1996 J MILLER

452



A / G-32 SECTION
BOX CULVERTS
SCALE: 1" = 2' (NOTE 1)
XREF: F96X0452



B / G-32 SECTION
BOX CULVERTS
(NOTE 4)
SCALE: 1" = 2' (NOTE 1)
XREF: F96X0453

45 / G-32



44 / G-12 PLAN
BOX CULVERTS
(NOTE 4)
SCALE: 1" = 10'
XREF: F96X5496



	T	A	B
SIDEWALL	7"	3 5/16"	3 1/16"
TOP SLAB	8"	4 5/16"	4 1/16"
BOTTOM SLAB	7"	3 5/16"	3 1/16"

45 / G-32 DETAIL
BOX CULVERT JOINT
SCALE: 1" = 3"
XREF: F96X0453

NOTES:

1. DETAILS ARE SHOWN TO SCALE AS NOTED EXCEPT FOR THE GEOSYNTHETICS WHICH ARE SHOWN AT AN EXAGGERATED SCALE FOR CLARITY. MATERIAL TOLERANCES SHALL BE WITHIN THE LIMITS GIVEN IN THE SPECIFICATIONS.
2. BOX CULVERTS AND JOINTS SHALL BE IN ACCORDANCE WITH SECTION 02721 OF THE OSDF SPECIFICATIONS.
3. TRENCHING AND BACKFILLING SHALL BE IN ACCORDANCE WITH SECTION 02215 OF THE OSDF SPECIFICATIONS.
4. RIPRAP SHALL EXTEND 2 FEET VERTICALLY UP THE ACCESS CORRIDOR EMBANKMENT AT THE BOX CULVERT ENTRANCE AND EXIT.
5. CONSTRUCTION CONTROL POINT TABLES ARE PROVIDED ON DRAWINGS G-38 AND G-39.

REV. NO.	DATE	DESCRIPTION	DES BY	DR BY	CHK BY	RVW BY	APP BY
G	11.10.96	FINAL SUBMITTAL TO EPA	PR	RD	DLVL	KWC	RB
F	25.06.96	PREFINAL SUBMITTAL TO EPA					

SCALE AS SHOWN

FOR INFORMATION ONLY

OWNER/FACILITY:
UNITED STATES DEPARTMENT OF ENERGY
FERNALD ENVIRONMENTAL MANAGEMENT PROJECT

CLIENT:

FERMCO Fernald Environmental Restoration Management Corporation
PROJECT:
ON-SITE DISPOSAL FACILITY 478

TITLE:
STORMWATER MANAGEMENT SYSTEM DETAILS III
24007-23

THIS DRAWING MAY NOT BE ISSUED FOR PROJECT TENDER OR CONSTRUCTION, UNLESS SEALED.

Rudolph Bonaparte
SIGNATURE
8 Oct 1996
DATE

STATE OF OHIO
RUDOLPH BONAPARTE
E-56679
REGISTERED PROFESSIONAL ENGINEER

GeoSyntec Consultants
1100 LAKE HEARN DRIVE
ATLANTA, GEORGIA 30342 USA

FERMCO PROJECT NO.:	20100
FERMCO SUBCONTRACT NO.:	95PS005028
FERMCO DRAWING NO.:	90X-6000-G-00042
GEOSYNTEC PROJECT NO.:	GE3900-13.1
GEOSYNTEC DOCUMENT NO.:	F96-0151
SHEET NO.:	G-32
REVISION NO.:	G

FINAL DESIGN PACKAGE

M:\GACADD\GE3900-13\F96-0151 Sat Oct 05 11:34:40 1996 FERMCO/DUNN

452



122 G-2 **PLAN**
EQUIPMENT DECONTAMINATION FACILITY
(NOTE 8)
SCALE 1" = 4'
XREF: F96XG003



A G-37 **SECTION**
EQUIPMENT DECONTAMINATION FACILITY
(NOTES 3 AND 4)
SCALE: 1" = 4'
XREF: F96XG004



125 G-37 **DETAIL**
PIPE COLLAR
(NOTE 1)
SCALE: 1" = 6"
XREF: F96XG002



124 G-37 **SECTIONAL PLAN**
EQUIPMENT DECONTAMINATION FACILITY MANHOLE COVER SLAB
SCALE: 1" = 2'
XREF: F96XG002



123 G-37 **SECTIONAL PLAN**
EQUIPMENT DECONTAMINATION FACILITY MANHOLE
(NOTES 2 AND 5)
SCALE: 1" = 1'
XREF: F96XG005



C G-37 **SECTION**
EQUIPMENT DECONTAMINATION FACILITY MANHOLE COVER SLAB
SCALE: 1" = 2'
XREF: F96XG002



B G-37 **SECTION**
EQUIPMENT DECONTAMINATION FACILITY
(NOTES 1, 2, AND 7)
SCALE: 1" = 4'
XREF: F96XG003

NOTES:

1. MANHOLE, PIPES, AND FITTINGS SHALL BE IN ACCORDANCE WITH SECTION 02605 OF THE OSDF SPECIFICATIONS.
2. FRAME AND ACCESS COVER, PUMP, WIND/OVERSPRAY SHIELD, VALVES, AND CONNECTION FROM PUMP OUTLET TO CHECK VALVE SHALL BE IN ACCORDANCE WITH SECTION 15000 OF THE OSDF SPECIFICATIONS.
3. DETAILS ARE SHOWN TO SCALE AS NOTED EXCEPT OF THE GEOSYNTHETICS WHICH ARE SHOWN TO AN EXAGGERATED SCALE FOR CLARITY. MATERIAL TOLERANCES SHALL BE WITHIN THE LIMITS GIVEN IN THE OSDF SPECIFICATIONS.
4. SUBCONTRACTOR SHALL SLOPE GROUND SURROUNDING EQUIPMENT DECONTAMINATION FACILITY TO PREVENT STORMWATER RUNON.
5. SUBCONTRACTOR SHALL PERIODICALLY REMOVE SEDIMENT FROM THE EQUIPMENT DECONTAMINATION FACILITY MANHOLE TO MAINTAIN EFFICIENT OPERATIONS.
6. RAILROAD TIES SHALL BE 6"X8" CRESOTE-TREATED. RAILROAD TIE JOINTS SHALL BE STAGGERED IN ROADBED.
7. MECHANICAL COMPONENTS INSIDE MANHOLE ARE NOT SHOWN IN THIS SECTION.
8. CONSTRUCTION CONTROL POINT TABLES ARE PROVIDED ON DRAWINGS G-38.
9. TRENCHING AND BACKFILLING SHALL BE IN ACCORDANCE WITH SECTION 02215 OF THE OSDF SPECIFICATIONS.
10. PERFORATIONS IN EQUIPMENT DECONTAMINATION MANHOLE SHALL BE 5/8-INCH DIAMETER SPACED 120 DEGREES ON CENTER HORIZONTALLY AND 2-INCHES ON CENTER VERTICALLY. OFFSET PERFORATIONS IN ADJACENT ROWS BY 60 DEGREES.
11. FLEXIBLE STAINLESS STEEL DISCHARGE PIPE SHALL BE CONNECTED AT THE 90° ELBOW (AT CHECK VALVE) AND 1 1/2-INCH PUMP OUTLET, AND SHALL BE IN ACCORDANCE WITH SPECIFICATION SECTION 13000.
12. 2"X6" NO. 2 PRESSURE TREATED BOARDS SHALL BE NAILED TO RAILROAD TIES USING 20d NAILS.

REV. NO:	DATE	DESCRIPTION	DES BY	DR BY	CHK BY	RVW BY	APP BY
G	11.10.96	FINAL SUBMITTAL TO EPA	KLO	AHF	LA	KWC	LA
F	25.06.96	PREFINAL SUBMITTAL TO EPA					

FOR INFORMATION ONLY

OWNER/FACILITY:
UNITED STATES DEPARTMENT OF ENERGY
FERNALD ENVIRONMENTAL MANAGEMENT PROJECT

CLIENT:
FERMCO FERNALD ENVIRONMENTAL RESTORATION MANAGEMENT CORPORATION

PROJECT:
ON-SITE DISPOSAL FACILITY 479

TITLE:
EQUIPMENT DECONTAMINATION FACILITY DETAILS
240017_24

THIS DRAWING MAY NOT BE ISSUED FOR PROJECT TENDER OR CONSTRUCTION, UNLESS SEALED.

STATE OF OHIO — RUDOLPH BONAPARTE — E-56679 — REGISTERED PROFESSIONAL ENGINEER

Rudolph Bonaparte
SIGNATURE
8 Oct 1996
DATE

GeoSyntec Consultants
1100 LAKE HEARN DRIVE
ATLANTA, GEORGIA 30342 USA

FERMCO PROJECT NO.:	20100
FERMCO SUBCONTRACT NO.:	95PS005028
FERMCO DRAWING NO.:	90X-6000-G-00043
GEOSYNTEC PROJECT NO.:	GE3900-13.1
GEOSYNTEC DOCUMENT NO.:	F96-0161
SHEET NO.:	G-37
REVISION NO.:	G

FINAL DESIGN PACKAGE

H:\F96-0161 Wed Oct 09 16:08:19 1996 J MILLER

452

SUBGRADE AT CELL OUTLET CONSTRUCTION CONTROL POINTS

CELL 1 CONTROL POINTS				CELL 2 CONTROL POINTS				CELL 3 CONTROL POINTS				CELL 4 CONTROL POINTS				CELL 5 CONTROL POINTS				CELL 6 CONTROL POINTS				CELL 7 CONTROL POINTS				CELL 8 CONTROL POINTS				CELL 9 CONTROL POINTS			
POINT NO.	NORTHING	EASTING	ELEVATION	POINT NO.	NORTHING	EASTING	ELEVATION	POINT NO.	NORTHING	EASTING	ELEVATION	POINT NO.	NORTHING	EASTING	ELEVATION	POINT NO.	NORTHING	EASTING	ELEVATION	POINT NO.	NORTHING	EASTING	ELEVATION	POINT NO.	NORTHING	EASTING	ELEVATION	POINT NO.	NORTHING	EASTING	ELEVATION	POINT NO.	NORTHING	EASTING	ELEVATION
1001	482980.20	1350855.06	598.22	1010	482580.23	1350850.17	595.22	1019	482180.26	1350845.28	592.22	1028	481780.29	1350840.40	589.22	1037	481380.32	1350835.51	586.22	1046	480980.35	1350830.62	583.22	1055	480580.40	1350823.73	581.20	1064	480180.43	1350818.84	579.20	1073	479780.46	1350813.96	577.20
1002	482980.40	1350838.33	598.06	1011	482580.43	1350833.44	595.06	1020	482180.46	1350828.56	592.06	1029	481780.49	1350823.67	589.06	1038	481380.52	1350818.78	586.06	1047	480980.55	1350813.89	583.06	1056	480580.60	1350807.08	581.04	1065	480180.63	1350802.19	579.04	1074	479780.66	1350797.30	577.04
1003	482964.40	1350838.14	598.06	1012	482564.43	1350833.25	595.06	1021	482164.46	1350828.36	592.06	1030	481764.49	1350823.47	589.06	1039	481364.52	1350818.58	586.06	1048	480964.55	1350813.69	583.06	1057	480564.61	1350806.88	581.04	1066	480164.64	1350802.00	579.04	1075	479764.67	1350797.11	577.04
1004	482964.20	1350854.40	598.22	1013	482564.23	1350849.52	595.22	1022	482164.26	1350844.63	592.22	1031	481764.29	1350839.74	589.22	1040	481364.32	1350834.85	586.22	1049	480964.35	1350829.96	583.22	1058	480564.41	1350823.23	581.20	1067	480164.44	1350818.34	579.20	1076	479764.47	1350813.45	577.20
1005	482958.83	1350832.48	603.64	1014	482558.86	1350827.60	600.64	1023	482158.89	1350822.71	597.64	1032	481758.92	1350817.82	594.64	1041	481358.95	1350812.93	591.64	1050	480958.98	1350808.04	588.64	1059	480558.99	1350801.19	586.67	1068	480159.02	1350796.30	584.67	1077	479759.05	1350791.41	582.67
1006	482986.39	1350832.55	603.92	1015	482586.42	1350827.66	600.92	1024	482186.45	1350822.77	597.92	1033	481786.48	1350817.88	594.92	1042	481386.51	1350812.99	591.92	1051	480986.54	1350808.10	588.92	1060	480586.55	1350801.34	586.85	1069	480186.58	1350796.45	584.85	1078	479786.61	1350791.56	582.85
1007	482977.27	1350848.90	598.16	1016	482577.30	1350844.02	595.16	1025	482177.33	1350839.13	592.16	1034	481777.36	1350834.24	589.16	1043	481377.39	1350829.35	586.16	1052	480977.42	1350824.46	583.16	1061	480577.48	1350817.58	581.14	1070	480177.51	1350812.69	579.14	1079	479777.54	1350807.80	577.14
1008	482972.36	1350842.10	598.09	1017	482572.38	1350837.22	595.09	1026	482172.41	1350832.33	592.09	1035	481772.44	1350827.44	589.09	1044	481372.47	1350822.55	586.09	1053	480972.50	1350817.66	583.09	1062	480572.56	1350810.77	581.07	1071	480172.59	1350805.89	579.07	1080	479772.62	1350801.00	577.07
1009	482967.31	1350845.45	598.13	1018	482567.34	1350840.56	595.13	1027	482167.37	1350835.68	592.13	1036	481767.40	1350830.79	589.13	1045	481367.43	1350825.90	586.13	1054	480967.46	1350821.01	583.13	1063	480567.52	1350814.12	581.11	1072	480167.55	1350809.23	579.11	1081	479767.58	1350804.35	577.11

COMPACTED CLAY LINER AT CELL OUTLET CONSTRUCTION CONTROL POINTS

CELL 1 CONTROL POINTS				CELL 2 CONTROL POINTS				CELL 3 CONTROL POINTS				CELL 4 CONTROL POINTS				CELL 5 CONTROL POINTS				CELL 6 CONTROL POINTS				CELL 7 CONTROL POINTS				CELL 8 CONTROL POINTS				CELL 9 CONTROL POINTS			
POINT NO.	NORTHING	EASTING	ELEVATION	POINT NO.	NORTHING	EASTING	ELEVATION	POINT NO.	NORTHING	EASTING	ELEVATION	POINT NO.	NORTHING	EASTING	ELEVATION	POINT NO.	NORTHING	EASTING	ELEVATION	POINT NO.	NORTHING	EASTING	ELEVATION	POINT NO.	NORTHING	EASTING	ELEVATION	POINT NO.	NORTHING	EASTING	ELEVATION	POINT NO.	NORTHING	EASTING	ELEVATION
2001	482980.16	1350855.42	601.23	2009	482580.19	1350850.53	598.23	2017	482180.22	1350845.64	595.23	2025	481780.25	1350840.75	592.23	2033	481380.28	1350835.86	589.23	2041	480980.31	1350830.97	586.23	2049	480580.37	1350824.09	584.21	2057	480180.40	1350819.20	582.21	2065	479780.43	1350814.31	580.21
2002	482964.23	1350854.76	601.22	2010	482564.26	1350849.87	598.22	2018	482164.29	1350844.99	595.22	2026	481764.32	1350840.10	592.22	2034	481364.35	1350835.21	589.22	2042	480964.38	1350830.32	586.22	2050	480564.43	1350823.59	584.20	2058	480164.46	1350818.70	582.20	2066	479764.49	1350813.81	580.20
2003	482975.18	1350856.84	601.24	2011	482575.21	1350851.95	598.24	2019	482175.24	1350847.06	595.24	2027	481775.26	1350842.17	592.24	2035	481375.29	1350837.28	589.24	2043	480975.32	1350832.39	586.24	2051	480575.38	1350825.51	584.22	2059	480175.41	1350820.62	582.22	2067	479775.44	1350815.73	580.22
2004	482979.26	1350849.88	602.60	2012	482579.29	1350845.00	599.60	2020	482179.32	1350840.11	596.60	2028	481779.35	1350835.22	593.60	2036	481379.38	1350830.33	590.60	2044	480979.41	1350825.44	587.60	2052	480579.46	1350818.56	585.58	2060	480179.49	1350813.67	583.58	2068	479779.52	1350808.78	581.58
2005	482970.26	1350850.00	602.48	2013	482570.29	1350845.11	599.48	2021	482170.32	1350840.23	596.48	2029	481770.35	1350835.34	593.48	2037	481370.38	1350830.45	590.48	2045	480970.41	1350825.56	587.48	2053	480570.46	1350818.67	585.46	2061	480170.49	1350813.78	583.46	2069	479770.52	1350808.90	581.46
2006	482974.35	1350842.79	604.32	2014	482574.38	1350837.91	601.32	2022	482174.41	1350833.02	598.32	2030	481774.44	1350828.13	595.32	2038	481374.47	1350823.24	592.32	2046	480974.50	1350818.35	589.32	2054	480574.55	1350811.46	587.30	2062	480174.58	1350806.58	585.30	2070	479774.61	1350801.69	583.30
2007	482965.22	1350853.17	601.63	2015	482565.25	1350848.28	598.63	2023	482165.28	1350843.39	595.63	2031	481765.31	1350838.50	592.63	2039	481365.34	1350833.61	589.63	2047	480965.37	1350828.73	586.63	2055	480565.42	1350821.84	584.61	2063	480165.45	1350816.95	582.61	2071	479765.48	1350812.06	580.61
2008	482969.31	1350845.96	603.48	2016	482569.34	1350841.07	600.48	2024	482169.37	1350836.18	597.48	2032	481769.40	1350831.29	594.48	2040	481369.43	1350826.41	591.48	2048	480969.46	1350821.52	588.48	2056	480569.51	1350814.63	586.46	2064	480169.54	1350809.74	584.46	2072	479769.57	1350804.85	582.46

LEAK DETECTION SYSTEM AT CELL OUTLET CONSTRUCTION CONTROL POINTS

CELL 1 CONTROL POINTS				CELL 2 CONTROL POINTS				CELL 3 CONTROL POINTS				CELL 4 CONTROL POINTS				CELL 5 CONTROL POINTS				CELL 6 CONTROL POINTS				CELL 7 CONTROL POINTS				CELL 8 CONTROL POINTS				CELL 9 CONTROL POINTS			
POINT NO.	NORTHING	EASTING	ELEVATION	POINT NO.	NORTHING	EASTING	ELEVATION	POINT NO.	NORTHING	EASTING	ELEVATION	POINT NO.	NORTHING	EASTING	ELEVATION	POINT NO.	NORTHING	EASTING	ELEVATION	POINT NO.	NORTHING	EASTING	ELEVATION	POINT NO.	NORTHING	EASTING	ELEVATION	POINT NO.	NORTHING	EASTING	ELEVATION	POINT NO.	NORTHING	EASTING	ELEVATION
3001	482984.17	1350835.55	607.27	3014	482584.20	1350830.66	604.27	3027	482184.23	1350825.77	601.27	3040	481784.26	1350820.88	598.27	3053	481384.29	1350815.99	595.27	3066	480984.32	1350811.10	592.27	3079	480584.49	1350804.18	590.25	3092	480184.52	1350799.29	588.25	3105	479784.55	1350794.40	586.25
3002	482983.92	1350855.40	602.30	3015	482583.95	1350850.51	599.30	3028	482183.98	1350845.62	596.30	3041	481784.01	1350840.73	593.30	3054	481384.04	1350835.85	590.30	3067	480984.07	1350830.96	587.30	3080	480584.24	1350824.03	585.28	3093	480184.27	1350819.14	583.28	3106	479784.30	1350814.25	581.28
3003	482980.11	1350859.27	602.27	3016	482580.14	1350854.38	599.27	3029	482180.17	1350849.49	596.27	3042	481780.20	1350844.60	593.27	3055	481380.23	1350839.72	590.27	3068	480980.26	1350834.83	587.27	3081	480580.31	1350828.02	585.25	3094	480180.34	1350823.13	583.25	3107	479780.37	1350818.24	581.25
3004	482964.19	1350859.08	602.27	3017	482564.22	1350854.19	599.27	3030	482164.25	1350849.30	596.27	3043	481764.28	1350844.41	593.27	3056	481364.31	1350839.52	590.27	3069	480964.34	1350834.63	587.27	3082	480564.39	1350827.82	585.25	3095	480164.42	1350822.93	583.25	3108	479764.45	1350818.05	581.25
3005	482959.75	1350854.35	602.31	3018	482559.78	1350849.46	599.31	3031	482159.81	1350844.57	596.31	3044	481759.84	1350839.69	593.31	3057	481359.87	1350834.80	590.31	3070	480959.90	1350829.91	587.31	3083	480560.08	1350823.23	585.29	3096	480160.11	1350818.34	583.29	3109	479760.14	1350813.45	581.29
3006	482959.99	1350834.53	607.27	3019	482560.02	1350829.64	604.27	3032	482160.05	1350824.75	601.27	3045	481760.08	1350819.86	598.27	3058	481360.11	1350814.97	595.27	3071	480960.14	1350810.08	592.27	3084	480560.32	1350803.40	590.25	3097	480160.35	1350798.51	588.25	3110	479760.38	1350793.62	586.25
3007	482964.43	1350839.08	607.27	3020	482564.46	1350834.19	604.27	3033	482164.49	1350829.30	601.27	3046	481764.52	1350824.41	598.27	3059	481364.55	1350819.52	595.27	3072	480964.58	1350814.63	592.27	3085	480564.63	1350807.82	590.25	3098	480164.66	1350802.94	588.25	3111	479764.69	1350798.05	586.25
3008	482980.35	1350839.27	607.27	3021	482580.38	1350834.38	604.27	3034	482180.41	1350829.49	601.27	3047	481780.44	1350824.61	598.27	3060	481380.47	1350819.72	595.27	3073	480980.50	1350814.83	592.27	3086	480580.56	1350808.02	590.25	3099	480180.58	1350803.13	588.25	3112	479780.61	1350798.24	586.25
3009	482972.14	1350860.01	602.27	3022	482572.17	1350855.12	599.27	3035	482172.20	1350850.23	596.27	3048	481772.23	1350845.34	593.27	3061	481372.26	1350840.45	590.27	3074	480972.29	1350835.56	587.27	3087	480572.34	1350828.75	585.25	3100	480172.37	1350823.86	583.25	3113	479772.40	1350818.98	581.25
3010	482970.17	1350857.27	602.73	3023	482570.20	1350852.38	599.74	3036	482170.23	1350847.49	596.74	3049	481770.26	1350842.60	593.74	3062	481370.29	1350837.71	590.74	3075	480970.32	1350832.83	587.74	3088	480570.37	1350826.01	585.72	3101	480170.40	1350821.13	583.72	3114	479770.43	1350816.24	581.72
3011	482974.25	1350851.03	604.31	3024	482574.28	1350846.14	601.31	3037	482174.31	1350841.25	598.31	3050	481774.34	1350836.36	595.31	3063	481374.37	1350831.47	592.31	3076	480974.40	1350826.59	589.31	3089	480574.45	1350819.77	587.29	3102	480174.48	1350814.89	585.29	3115	479774.51	1350810.00	583.29
3012	482965.12	1350861.11	602.29	3025	482565.15	1350856.22	599.29	3038	482165.18	1350851.33	596.29	3051	481765.21	1350846.44	593.29	3064	481365.24	1350841.55	590.29	3077	480965.27	1350836.66	587.29	3090	480565.33	1350829.85	585.27	3103	480165.35	1350824.97	583.27	3116	479765.38	1350820.08	581.27
3013	482969.20	1350854.66	603.39	3026	482569.23	1350849.77	600.39	3039	482169.26	1350844.88	597.39	3052	481769.29	1350839.99	594.39	3065	481369.32	1350835.10	591.39	3078	480969.35	1350830.21	588.39	3091	480569.40	1350823.40	586.37	3104	480169.43	1350818.51	584.37	3117	479769.46	1350813.63	582.37

LEACHATE COLLECTION SYSTEM AT CELL OUTLET CONSTRUCTION CONTROL POINTS

CELL 1 CONTROL POINTS				CELL 2 CONTROL POINTS				CELL 3 CONTROL POINTS				CELL 4 CONTROL POINTS				CELL 5 CONTROL POINTS				CELL 6 CONTROL POINTS				CELL 7 CONTROL POINTS				CELL 8 CONTROL POINTS				CELL 9 CONTROL POINTS			
POINT NO.	NORTHING	EASTING	ELEVATION	POINT NO.	NORTHING	EASTING	ELEVATION	POINT NO.	NORTHING	EASTING	ELEVATION	POINT NO.	NORTHING	EASTING	ELEVATION	POINT NO.	NORTHING	EASTING	ELEVATION	POINT NO.	NORTHING	EASTING	ELEVATION	POINT NO.	NORTHING	EASTING	ELEVATION	POINT NO.	NORTHING	EASTING	ELEVATION	POINT NO.	NORTHING	EASTING	ELEVATION
4001	482984.14	1350835.67	608.26	4011	482584.17	1350830.78	605.26	4021	482184.20	1350825.89	602.26	4031	481784.23	1350821.01	599.26	4041	481384.26	1350816.12	596.26	4051	480984.29	1350811.23	593.26	4061	480584.35	1350804.30	591.24	4071	480184.38	1350799.42	589.24	4081	479784.41	1350794.53	587.24
4002	482983.90	1350855.52	603.30	4012	482583.93	1350850.63	600.30	4022	482183.96	1350845.74	597.30	4032	481783.99	1350840.85	594.30	4042	481384.02	1350835.97	591.30	4052	480984.05	1350831.08	588.30	4062	480584.11	1350824.15	586.28	4072	480184.14	1350819.26	584.28	4082	479784.17	1350814.38	582.28
4003	482983.83	1350855.59	603.30	4013	482583.86	1350850.70	600.30	4023	482183.89	1350845.81	597.30	4033	481783.92	1350840.92	594.30	4043	481383.95	1350836.03	591.30	4053	480983.98	1350831.15	588.30	4063	480584.04	1350824.16	586.28	4073	480184.07	1350819.27	584.28	4083	479784.10	1350814.38	582.28
4004	482980.13	1350855.54	604.23	4014	482580.16	1350850.65	601.23	4024	482180.19	1350845.76	598.23	4034	481780.22	1350840.88	595.23	4044	481380.25	1350835.99	592.23	4054	480980.28	1350831.10	589.23	4064	480580.34	1350824.18	587.21	4074	480180.37	1350819.29	585.21	4084	479780.40	1350814.40	583.21
4005	482964.25	1350855.35	604.23	4015	482564.28	1350850.46	601.23	4025	482164.31	1350845.57	598.23	4035	481764.34	1350840.68	595.23	4045	481364.37	1350835.79	592.23	4055	480964.40	1350830.91	589.23	4065	480564.46	1350823.98	587.21	4075	480164.49	1350819.09	585.21	4085	479764.52	1350814.21	583.21
4006	482960.55	1350855.30	603.30	4016	482560.58	1350850.41	600.30	4026	482160.61	1350845.53	597.30	4036	481760.64	1350840.64	594.30	4046	481360.67	1350835.75	591.30	4056	480960.70	1350830.86	588.30	4066	480560.75	1350823.94	586.28	4076	480160.78	1350819.05	584.28	4086	479760.81	1350814.16	582.28
4007	482959.77	1350854.47	603.31	4017	482559.80	1350849.58	600.31	4027	482159.83	1350844.69	597.31	4037	481759.86	1350839.80	594.31	4047	481359.89	1350834.92	591.31	4057	480959.92	1350830.03	588.31	4067	480560.22	1350823.36	586.29	4077	480160.25	1350818.48	584.29	4087	479760.28	1350813.59	582.29
4008	482960.01	1350834.65	608.26	4018	482560.04	1350829.76	605.26	4028	482160.07	1350824.87	602.26	4038	481760.10	1350819.99	599.26	4048	481360.13	1350815.10	596.26	4058	480960.16	1350810.21	593.26	4068	480560.46	1350803.32	591.24	4078	480160.49	1350798.45	589.24	4088	479760.52	1350793.76	587.24
4009	482964.45	1350839.20	608.26	4019	482564.48	1350834.31	605.26	4029	482164.51	1350829.42	602.26	4039	481764.54	1350824.53	599.26	4049	481364.57	1350819.65	596.26	4059	480964.60	1350814.76	593.26	4069	480564.65	1350807.84	591.24	4079	480164.68	1350802.95	589.24	4089	479764.71	1350798.06	587.24
4010	482980.33	1350839.39	608.26	4020	482580.36	1350834.51	605.26	4030	482180.39	1350829.62	602.26	4040	481780.42	1350824.73	599.26	4050	481380.45	1350819.84	596.26	4060	480980.48	1350814.95	593.26	4070	480580.53	1350808.03	591.24	4080	480180.56	1350803.14	589.24	4090	479780.59	1350798.25	587.24

LDS AND LCS MANHOLES CONSTRUCTION CONTROL POINTS

CELL 1 CONTROL POINTS				CELL 2 CONTROL POINTS				CELL 3 CONTROL POINTS				CELL 4 CONTROL POINTS				CELL 5 CONTROL POINTS				CELL 6 CONTROL POINTS				CELL 7 CONTROL POINTS				CELL 8 CONTROL POINTS				CELL 9 CONTROL POINTS			
POINT NO.	NORTHING	EASTING	ELEVATION	POINT NO.	NORTHING	EASTING	ELEVATION	POINT NO.	NORTHING	EASTING	ELEVATION	POINT NO.	NORTHING	EASTING	ELEVATION	POINT NO.	NORTHING	EASTING	ELEVATION	POINT NO.	NORTHING	EASTING	ELEVATION	POINT NO.	NORTHING	EASTING	ELEVATION	POINT NO.	NORTHING	EASTING	ELEVATION	POINT NO.	NORTHING	EASTING	ELEVATION
7101	482983.26	1350688.79	594.34	7201	482583.29	1350683.91	591.34	7301	482183.32	1350679.02	588.34	7401	481783.35	1350674.13	585.34	7501	481383.38	1350669.24	582.34	7601	480983.41	1350664.35	579.34	7701	480583.44	1350659.46	576.84	7801	480183.47	1350654.58	574.84	7901	479783.50	1350649.69	572.84
7102	482979.20	1350691.03	594.34	7202	482579.23	1350686.14	591.34	7302	482179.26	1350681.25	588.34	7402	481779.29	1350676.36	585.34	7502	481379.32	1350671.47	582.34	7602	480979.35	1350666.59	579.34	7702	480579.38	1350661.70	576.84	7802	480179.41	1350656.81	574.84	7902	479779.44	1350651.92	572.84
7103	482975.29	1350683.86	594.34	7203	482575.29	1350678.97	591.34	7303	482175.32	1350674.08	588.34	7403	481775.35	1350669.19	585.34	7503	481375.38	1350664.31	582.34	7603	480975.41	1350659.42	579.34	7703	480575.44	1350654.53	576.84	7803	480175.47	1350649.64	574.84	7903	479775.50	1350644.75	572.84
7104	482973.33	1350682.67	594.34	7204	482573.36	1350677.78	591.34	7304	482173.39	1350672.90	588.34	7404	481773.42	1350668.01	585.34	7504	481373.45	1350663.12	582.34	7604	480973.48	1350658.23	579.34	7704	480573.51	1350653.34	576.84	7804	480173.54	1350648.45	574.84	7904	479773.57	1350643.57	572.84
7105	482969.28	1350684.91	594.34	7205	482569.31	1350680.02	591.34	7305	482169.34	1350675.13	588.34	7405	481769.37	1350670.24	585.34	7505	481369.40	1350665.35	582.34	7605	480969.43	1350660.46	579.34	7705	480569.46	1350655.58	576.84	7805	480169.49	1350650.69	574.84	7905	479769.51	1350645.80	572.84
7106	482965.33	1350677.74	594.34	7206	482565.36	1350672.85	591.34	7306	482165.39	1350667.96	588.34	7406	481765.42	1350663.07	585.34	7506	481365.45	1350658.18	582.34	7606	480965.48	1350653.30	579.34	7706	480565.51	1350648.41	576.84	7806	480165.54	1350643.52	574.84	7906	479765.57	1350638.63	572.84

DRAINAGE CHANNEL GRAVITY INLET STRUCTURES CONSTRUCTION CONTROL POINTS

CELL 1 CONTROL POINTS				CELL 2 CONTROL POINTS				CELL 3 CONTROL POINTS				CELL 4 CONTROL POINTS				CELL 5 CONTROL POINTS				CELL 6 CONTROL POINTS				CELL 7 CONTROL POINTS				CELL 8 CONTROL POINTS				CELL 9 CONTROL POINTS			
POINT NO.	NORTHING	EASTING	ELEVATION	POINT NO.	NORTHING	EASTING	ELEVATION	POINT NO.	NORTHING	EASTING	ELEVATION	POINT NO.	NORTHING	EASTING	ELEVATION	POINT NO.	NORTHING	EASTING	ELEVATION	POINT NO.	NORTHING	EASTING	ELEVATION	POINT NO.	NORTHING	EASTING	ELEVATION	POINT NO.	NORTHING	EASTING	ELEVATION	POINT NO.	NORTHING	EASTING	ELEVATION
8101	482996.85	1350685.80	598.71	8201	482596.88	1350680.91	595.71	8301	482196.91	1350676.02	592.71	8401	481796.94	1350671.14	589.71	8501	481396.97	1350666.25	586.71	8601	480997.00	1350661.36	583.71	8701	480597.03	1350656.47	581.16	8801	480197.06	1350651.58	579.16	8901	479797.09	1350646.69	577.16
8102	482994.99	1350687.61	598.71	8202	482595.02	1350682.72	595.71	8302	482195.05	1350677.84	592.71	8402	481795.08	1350672.95	589.71	8502	481395.11	1350668.06	586.71	8602	480995.14	1350663.17	583.71	8702	480595.17	1350658.28	581.16	8802	480195.20	1350653.39	579.16	8902	479795.23	1350648.50	577.16
8103	482993.18	1350685.76	598.71	8203	482593.21	1350680.87	595.71	8303	482193.24	1350675.98	592.71	8403	481793.27	1350671.09	589.71	8503	481393.30	1350666.20	586.71	8603	480993.33	1350661.31	583.71	8703	480593.36	1350656.43	581.16	8803	480193.39	1350651.54	579.16	8903	479793.42	1350646.65	577.16
8104	482995.04	1350683.95	598.71	8204	482595.07	1350679.06	595.71	8304	482195.10	1350674.17	592.71	8404	481795.13	1350669.28	589.71	8504	481395.16	1350664.39	586.71	8604	480995.19	1350659.50	583.71	8704	480595.22	1350654.62	581.16	8804	480195.25	1350649.73	579.16	8904	479795.28	1350644.84	577.16
8105	482796.87	1350683.36	597.37	8205	482396.90	1350678.47	594.37	8305	481996.93	1350673.58	591.37	8405	481596.95	1350668.69	588.37	8505	481196.98	1350663.80	585.37	8605	480797.01	1350658.92	582.37	8705	480397.04	1350654.03	580.27	8805	479997.07	1350649.14	578.27				
8106	482795.01	1350685.17	597.37	8206	482395.04	1350680.28	594.37	8306	481995.07	1350675.39	591.37	8406	481595.10	1350670.50	588.37	8506	481195.13	1350665.61	585.37	8606	480795.16	1350660.73	582.37	8706	480395.19	1350655.84	580.27	8806	479995.22	1350650.95	578.27				
8107	482793.20	1350683.31	597.37	8207	482393.23	1350678.42	594.37	8307	481993.26	1350673.54	591.37	8407	481593.29	1350668.65	588.37	8507	481193.32	1350663.76	585.37	8607	480793.35	1350658.87	582.37	8707	480393.38	1350653.98	580.27	8807	479993.41	1350649.09	578.27				
8108	482795.05	1350681.50	597.37	8208	482395.08	1350676.61	594.37	8308	481995.11	1350671.72	591.37	8408	481595.14	1350666.84	588.37	8508	481195.17	1350661.95	585.37	8608	480795.20	1350657.06	582.37	8708	480395.23	1350652.17	580.27	8808	479995.26	1350647.28	578.27				

HORIZONTAL MONITORING WELLS CONSTRUCTION CONTROL POINTS

| CELL 1 CONTROL POINTS | | | | CELL 2 CONTROL POINTS | | | | CELL 3 CONTROL POINTS | | | | CELL 4 CONTROL POINTS | | | | CELL 5 CONTROL POINTS | | | | CELL 6 CONTROL POINTS | | | | CELL 7 CONTROL POINTS | | | | CELL 8 CONTROL POINTS | | | | CELL 9 CONTROL POINTS | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---

FINAL DESIGN PACKAGE

NOTE:
1. CONSTRUCTION SURVEY CONTROL IS GIVEN TO THE NEAREST HUNDREDTH OF A FOOT. CONSTRUCTION TOLERANCES SHALL BE IN ACCORDANCE WITH THE OSDF SPECIFICATIONS.

CONTOURING LAYER CONSTRUCTION CONTROL POINTS

POINT NO.	NORTHING	EASTING	ELEVATION	POINT NO.	NORTHING	EASTING	ELEVATION	POINT NO.	NORTHING	EASTING	ELEVATION
5000	4850953.26	1350835.11	620.10	5019	4807689.57	1351073.09	643.23				
5001	4851116.63	1350840.02	620.47	5020	4807707.26	1351015.26	642.70				
5002	4851136.32	1350851.50	620.85	5021	4807724.63	1350906.75	642.12				
5003	4851153.73	1350896.96	621.60	5022	4807742.07	1351015.26	642.45				
5004	4851153.90	1350879.49	621.80	5023	4807760.15	1351124.14	643.84				
5005	4851147.14	1351141.21	622.02	5024	4807900.64	1351441.14	643.15				
5006	4851134.18	1351464.58	622.04	5025	4807927.60	1351421.14	643.29				
5007	4851128.85	1351484.26	622.07	5026	4807953.21	1351397.65	643.02				
5008	4851085.12	1351501.56	622.11	5027	4807969.82	1350853.40	597.59				
5009	4851085.12	1351501.56	622.11	5028	4807969.38	1350830.05	597.46				
5010	4852879.48	1351533.90	654.05	5029	4807960.39	1350810.18	597.74				
5011	4852886.48	1351504.10	653.92	5030	4807946.85	1350797.39	597.21				
5012	4852923.15	1351273.37	659.40	5031	4807928.05	1350737.06	597.09				
5013	4852915.20	1351099.31	659.33	5032	4807899.89	1350723.44	597.00				
5014	4852842.54	1351118.40	663.19	5033	4807947.75	1351234.64	632.46				
5015	4852776.51	1351306.85	663.75	5034	4807984.05	1351051.27	632.55				
5016	4852664.48	1351473.20	663.98	5035	4807944.92	1350973.75	638.56				
5017	4852664.48	1351473.20	663.98	5036	4807944.92	1350973.75	638.56				
5018	4852664.48	1351473.20	663.98	5037	4807944.92	1350973.75	638.56				

FINAL COVER SYSTEM CONSTRUCTION CONTROL POINTS

POINT NO.	NORTHING	EASTING	ELEVATION	POINT NO.	NORTHING	EASTING	ELEVATION	POINT NO.	NORTHING	EASTING	ELEVATION
6001	4851311.41	1351511.94	609.08	6025	4832746.17	1351577.57	607.08				
6002	4851356.11	1351669.78	609.54	6026	4832723.44	1351784.19	607.92				
6003	4851398.47	1351617.38	610.00	6027	4832776.18	1352060.54	608.14				
6004	4851352.00	1351652.06	609.71	6028	4832781.11	1352057.94	608.77				
6005	4851315.68	1351659.29	609.42	6029	4832735.35	1352057.69	607.20				
6006	4851315.68	1351659.29	609.42	6030	4832720.88	1352021.69	607.29				
6007	4851315.46	1351682.98	609.42	6031	4832224.43	1352057.38	605.00				
6008	4851315.68	1351664.99	609.42	6032	4832106.00	1352076.58	604.00				
6009	4851315.68	1351664.99	609.42	6033	4832106.86	1352076.58	604.00				
6010	4852439.20	1351574.02	591.05	6034	4807766.09	1351308.01	646.13				
6011	4852440.79	1351497.60	590.78	6035	4807767.21	1351249.67	651.96				
6012	4852444.20	1351444.36	590.51	6036	4807768.29	1351161.05	656.19				
6013	4852459.26	1351444.36	590.51	6037	4807768.29	1351161.05	656.19				
6014	4852464.85	1351444.36	590.51	6038	4807770.09	1351014.10	646.13				
6015	4852459.26	1351444.36	590.51	6039	4807765.96	1350968.19	641.13				
6016	4852459.26	1351444.36	590.51	6040	4807765.96	1350968.19	641.13				
6017	4852459.26	1351444.36	590.51	6041	4807765.96	1350968.19	641.13				
6018	4852459.26	1351444.36	590.51	6042	4807765.96	1350968.19	641.13				
6019	4852459.26	1351444.36	590.51	6043	4807765.96	1350968.19	641.13				
6020	4852459.26	1351444.36	590.51	6044	4807765.96	1350968.19	641.13				
6021	4852459.26	1351444.36	590.51	6045	4807765.96	1350968.19	641.13				
6022	4852459.26	1351444.36	590.51	6046	4807765.96	1350968.19	641.13				
6023	4852459.26	1351444.36	590.51	6047	4807765.96	1350968.19	641.13				
6024	4852459.26	1351444.36	590.51	6048	4807765.96	1350968.19	641.13				

BORROW AREA CONSTRUCTION CONTROL POINTS

POINT NO.	NORTHING	EASTING	ELEVATION	POINT NO.	NORTHING	EASTING	ELEVATION	POINT NO.	NORTHING	EASTING	ELEVATION
6049	4792527.52	1351644.92	587.70	6066	4792724.67	1351644.11	587.54	6083	4792923.17	1351644.99	587.38
6050	4791941.88	1351644.73	588.00	6067	4792724.45	1351643.98	587.54	6084	4792923.17	1351644.99	587.38
6051	4791941.88	1351644.73	588.00	6068	4792724.45	1351643.98	587.54	6085	4792923.17	1351644.99	587.38
6052	4792244.45	1351644.43	587.90	6069	4792724.45	1351643.98	587.54	6086	4792923.17	1351644.99	587.38
6053	4792244.45	1351644.43	587.90	6070	4792724.45	1351643.98	587.54	6087	4792923.17	1351644.99	587.38
6054	4791941.88	1351644.73	588.00	6071	4792724.45	1351643.98	587.54	6088	4792923.17	1351644.99	587.38
6055	4791941.88	1351644.73	588.00	6072	4792724.45	1351643.98	587.54	6089	4792923.17	1351644.99	587.38
6056	4792244.45	1351644.43	587.90	6073	4792724.45	1351643.98	587.54	6090	4792923.17	1351644.99	587.38
6057	4792244.45	1351644.43	587.90	6074	4792724.45	1351643.98	587.54	6091	4792923.17	1351644.99	587.38
6058	4792244.45	1351644.43	587.90	6075	4792724.45	1351643.98	587.54	6092	4792923.17	1351644.99	587.38
6059	4792244.45	1351644.43	587.90	6076	4792724.45	1351643.98	587.54	6093	4792923.17	1351644.99	587.38
6060	4792244.45	1351644.43	587.90	6077	4792724.45	1351643.98	587.54	6094	4792923.17	1351644.99	587.38
6061	4792244.45	1351644.43	587.90	6078	4792724.45	1351643.98	587.54	6095	4792923.17	1351644.99	587.38
6062	4792244.45	1351644.43	587.90	6079	4792724.45	1351643.98	587.54	6096	4792923.17	1351644.99	587.38
6063	4792244.45	1351644.43	587.90	6080	4792724.45	1351643.98	587.54	6097	4792923.17	1351644.99	587.38
6064	4792244.45	1351644.43	587.90	6081	4792724.45	1351643.98	587.54	6098	4792923.17	1351644.99	587.38
6065	4792244.45	1351644.43	587.90	6082	4792724.45	1351643.98	587.54	6099	4792923.17	1351644.99	587.38

COMPACTED CLAY LINER CONSTRUCTION CONTROL POINTS

POINT NO.	NORTHING	EASTING	ELEVATION	POINT NO.	NORTHING	EASTING	ELEVATION	POINT NO.	NORTHING	EASTING	ELEVATION
2073	4830937.06	1350837.37	603.43	2105	4799411.04	1350807.01	583.32	2137	4801559.24	1351497.24	606.66
2074	4827895.26	1350825.80	604.43	2106	4799411.79	1350801.58	588.82	2138	4801559.49	1351497.05	606.66
2075	4827777.65	1350816.93	604.70	2107	4799594.07	1350853.46	584.02	2139	4801587.30	1351497.14	606.66
2076	4827777.65	1350816.52	604.70	2108	4799587.42	1351397.70	589.42	2140	4801756.73	1351460.83	598.43
2077	4827765.65	1350816.52	604.70	2109	4799587.42	1351397.70	589.42	2141	4801772.88	1351460.56	598.14
2078	4827765.65	1350816.52	604.70	2110	4799594.07	1350853.46	584.02	2142	4801772.88	1351460.56	598.14
2079	4827765.65	1350816.52	604.70	2111	4799772.80	1350812.04	583.32	2143	4801772.88	1351460.56	598.14
2080	4827765.65	1350816.52	604.70	2112	4799772.80	1350812.04	583.32	2144	4801772.88	1351460.56	598.14
2081	4827765.65	1350816.52	604.70	2113	4799772.80	1350812.04	583.32	2145	4801772.88	1351460.56	598.14
2082	4827765.65	1350816.52	604.70	2114	4799772.80	1350812.04	583.32	2146	4801772.88	1351460.56	598.14
2083	4827765.65	1350816.52	604.70	2115	4799772.80	1350812.04	583.32	2147	4801772.88	1351460.56	598.14
2084	4827765.65	1350816.52	604.70	2116	4799772.80	1350812.04	583.32	2148	4801772.88	1351460.56	598.14
2085	4827765.65	1350816.52	604.70	2117	4799772.80	1350812.04	583.32	2149	4801772.88	1351460.56	598.14
2086	4827765.65	1350816.52	604.70	2118	4799772.80	1350812.04	583.32	2150	4801772.88	1351460.56	598.14
2087	4827765.65	1350816.52	604.70	2119	4799772.80	1350812.04	583.32	2151	4801772.88	1351460.56	598.14
2088	4827765.65	1350816.52	604.70	2120	4799772.80	1350812.04	583.32	2152	4801772.88	1351460.56	598.14
2089	4827765.65	1350816.52	604.70	2121	4799772.80	1350812.04	583.32	2153	4801772.88	1351460.56	598.14
2090	4827765.65	1350816.52	604.70	2122	4799772.80	1350812.04	583.32	2154	4801772.88	1351460.56	598.14
2091	4827765.65	1350816.52	604.70	2123	4799772.80	1350812.04	583.32	2155	4801772.88	1351460.56	598.14
2092	4827765.65	1350816.52	604.70	2124	4799772.80	1350812.04	583.32	2156	4801772.88	1351460.56	598.14
2093	4827765.65	1350816.52	604.70	2125	4799772.80	1350812.04	583.32	2157	4801772.88	1351460.56	598.14
2094	4827765.65	1350816.52	604.70	2126	4799772.80	1350812.04	583.32	2158	4801772.88	1351460.56	598.14
2095	4827765.65	1350816.52	604.70	2127	4799772.80	1350812.04	583.32	2159	4801772.88	1351460.56	598.14
2096	4827765.65	1350816.52	604.70	2128	4799772.80	1350812.04	583.32	2160	4801772.88	1351460.56	598.14
2097	4827765.65	1350816.52	604.70	2129	4799772.80	1350812.04	583.32	2161	4801772.88	1351460.56	598.14
2098	4827765.65	1350816.52	604.70	2130	4799772.80	1350812.04	583.32	2162	4801772.88	1351460.56	598.14
2099	4827765.65	1350816.52	604.70	2131	4799772.80	1350812.04	583.32	2163	4801772.88	1351460.56	598.14
2100	4827765.65	1350816.52	604.70	2132	4799772.80	1350812.04	583.32	2164	4801772.88	1351460.56	598.14
2101	4827765.65	1350816.52	604.70	2133	4799772.80	1350812.04	583.32	2165	4801772.88	1351460.56	598.14
2102	4827765.65	1350816.52	604.70	2134	4799772.80	1350812.04	583.32	2166	4801772.88	1351460.56	598.14
2103	4827765.65	1350816.52	604.70	2135	4799772.80	1350812.04	583.32	2167	4801772.88	1351460.56	598.14
2104	4827765.65	1350816.52	604.70	2136	4799772.80	1350812.04	583.32	2168	4801772.88	1351460.56	598.14

SUBGRADE CONSTRUCTION CONTROL POINTS

POINT NO.	NORTHING	EASTING	ELEVATION	POINT NO.	NORTHING	EASTING	ELEVATION	POINT NO.	NORTHING	EASTING	ELEVATION	POINT NO.	NORTHING	EASTING	ELEVATION
1082	4831.36	1350898.76	616.42	1106	4823236.79	1350826.76	616.27	1130	4822726.07	1350826.76	616.27	1154	4822236.79	1350826.76	616.27
1083	4823093.07	1350851.02	600.22	1107	4823196.04	1350777.49	616.48	1131	4822726.28	1350777.49	616.48	1155	4822236.50	1350777.49	616.48
1084	4823255.50	1350829.50	602.75	1108	4823196.04	1350777.49	616.48	1132	4822726.28	1350777.49	616.48	1156	4822236.50	1350777.49	616.48
1085	4823256.43	1350829.50	602.75	1109	4823196.04	1350777.49	616.48	1133	4822726.28	1350777.49	616.48	1157	4822236.50	1350777.49	616.48
1086	4823256.43	1350829.50	602.75	1110	4823196.04	1350777.49	616.48	1134	4822726.28	1350777.49	616.48	1158	4822236.50	1350777.49	616.48
1087	4823256.43	1350829.67	602.75	1111	4823196.04	1350777.49	616.48	1135	4822726.28	1350777.49	616.48	1159	4822236.50	1350777.49	616.48
1088	4819363.45	1350819.72	596.22	1112	4823196.04	1350777.49	616.48	1136	4822726.28	1350777.49	616.48	1160	4822236.50	1350777.49	616.48
1089	4819363.45	1350819.72	596.22	1113	4823196.04	1350777.49	616.48	1137	4822726.28	1350777.49	616.48	1161	4822236.50	1350777.49	616.48
1090	4819363.48	1350819.72	596.22	1114	4823196.04	1350777.49	616.48	1138	4822726.28	1350777.49	616.48	1162	4822236.50	1350777.49	616.48
1091	4819363.93	1350829.90	596.28	1115	4823196.04	1350777.49	616.48	1139	4822726.28	1350777.49	616.48	1163	4822236.50	1350777.49	616.48
1092	4819363.78	1350829.90	596.28	1116	4823196.04	1350777.49	616.48	1140	4822726.28	1350777.49	616.48	1164	4822236.50	1350777.49	616.48
1093	4819363.62	1350807.31	596.88	1117	4823196.04	1350777.49	616.48	1141	4822726.28	1350777.49	616.48	1165	4822236.50	1350777.49	616.48
1094	4819363.01	1350807.31	596.88	1118	4823196.04	1350777.49	616.48	1142	4822726.28	1350777.49	616.48	1166	4822236.50	1350777.49	616.48
1095	4819363.01	1350807.31	596.88	1119	4823196.04	1350777.49	616.48	1143	4822726.28	1350777.49	616.48	1167	4822236.50	1350777.49	616.48
1096	4819363.01	1350807.31	596.88	1120	4823196.04	1350777.49	616.48	1144	4822726.28	1350777.49	616.48	1168	4822236.50	1350777.49	616.48
1097	4819363.01	1350807.31	596.88	1121	4823196.04	1350777.49	616.48	1145	4822726.28	1350777.49	616.48	1169	4822236.50	1350777.49	616.48
1098	4819363.01	1350807.31	596.88	1122	4823196.04	1350777.49	616.48	1146	4822726.28	1350777.49	616.48	1170	4822236.50	1350777.49	616.48
1099	4819363.01	1350807.31	596.88	1123	4823196.04	1350777.49	616.48	1147	4822726.28	1350777.49	616.48	1171	4822236.50	1350777.49	616.48
1100	4819363.01	1350807.31	596.88	1124	4823196.04	1350777.49	616.48	1148	4822726.28	1350777.49	616.48	1172	4822236.50	1350777.49	616.48
1101	4819363.01	1350807.31	596.88	1125	4823196.04	1350777.49	616.48	1149	4822726.28	1350777.49	616.48	1173	4822236.50	1350777.49	616.48
1102	4819363.01	1350807.31	596.88	1126	4823196.04	1350777.49	616.48	1150	4822726.28	1350777.49	616.48	1174	4822236.50	1350777.49	616.48
1103	4819363.01	1350807.31	596.88	1127	4823196.04	1350777.49	616.48	1151	4822726.28	1350777.49	616.48	1175	4822236.50	1350777.49	616.48
1104	4819363.01	1350807.31	596.88	1128	4823196.04	1350777.49	616.48	1152	4822726.28	1350777.49	616.48	1176	4822236.50	1350777.49	616.48
1105	4819363.01	1350807.31	596.88	1129	4823196.04	1350777.49	616.48	1153	4822726.28	1350777.49	616.48	1177	4822236.50	1350777.49	616.48
1106	4819363.01	1350807.31	596.88												
1107	4819363.01	1350807.31	596.88												
1108	4819363.01	1350807.31	596.88												
1109	4819363.01	1350807.31	596.88												
1110	4819363.01	1350807.31	596.88												
1111	4819363.01	1350807.31	596.88												
1112	4819363.01	1350807.31	596.88												
1113	4819363.01	1350807.31	596.88												
1114	4819363.01	1350807.31	596.88												
1115	4819363.01	1350807.31	596.88												

FOR INFORMATION ONLY

REV. NO.	DATE	DESCRIPTION	DES BY	DR BY	CHK BY	RVW BY	APP BY
F	26.06.96	PREFINAL SUBMITTAL TO EPA					
G	11.10.96	FINAL SUBMITTAL TO EPA	DLV.	RD	LA	KMC	RB

OWNER/FACILITY:
UNITED STATES DEPARTMENT OF ENERGY
FERNALD ENVIRONMENTAL MANAGEMENT PROJECT
(UNITED STATES OF AMERICA) DEPARTMENT OF ENERGY

CLIENT:
FERMCO Environmental Restoration Management Corporation
FERNALD ENVIRONMENTAL RESTORATION MANAGEMENT CORPORATION

PROJECT:
ON-SITE DISPOSAL FACILITY H81

TITLE:
CONSTRUCTION CONTROL POINTS II

J4001_24

THIS DRAWING MAY NOT BE ISSUED FOR PUBLICATION, UNLESS SEALED.

STATE OF OHIO
RUDOLPH BOUAFFITE
E-56679
REGISTERED PROFESSIONAL ENGINEER
8 Oct 1996
DATE

GeoSyntec Consultants
1100 LAKE HEARN DRIVE
ATLANTA, GEORGIA 30342 USA

FEMACO PROJECT NO.:	20100
FEMACO SUBCONTRACT NO.:	95F-500302B
FEMACO DRAWING NO.:	90X-6000-G-00045
GEOSYNTEC PROJECT NO.:	GC3900-13.1
GEOSYNTEC DOCUMENT NO.:	F96-G160
SHEET NO.:	G-39
REVISION NO.:	G

M:\GA\ATL2\GC3900~1\F96G160.DWG 1:1 Oct 10 10:38:15 1996 FERMCO\DANN

452



E G-11 SECTION
HORIZONTAL MONITORING WELL
SCALE: 1" = 10' HORIZONTAL
1" = 10' VERTICAL



129 G-40 PLAN
HORIZONTAL MONITORING WELL TRENCH LAYOUT AT CELL OUTLET
SCALE: 1" = 4'



126 G-40 PLAN
HORIZONTAL MONITORING WELL COVER SLAB
SCALE: 1" = 2'



127 G-40 DETAIL
HORIZONTAL MONITORING WELL TRENCH AT CELL OUTLET
SCALE: 1" = 4'



130 G-40 DETAIL
HORIZONTAL MONITORING WELL
SCALE: 1" = 2'



128 G-40 DETAIL
HORIZONTAL MONITORING WELL EMBEDMENT
SCALE: 1" = 1'

LOCATION OF OVERLYING FEATURE RELATIVE TO TRENCH

LEGEND:

- ⊕A LDS PIPE SECONDARY LINER PENETRATION
- ⊕B REDUNDANT LCS PIPE SECONDARY LINER PENETRATION
- ⊕C REDUNDANT LCS PIPE PRIMARY LINER PENETRATION
- ⊕D LCS PIPE SECONDARY LINER PENETRATION
- ⊕E LCS PIPE PRIMARY LINER PENETRATION

NOTES:

1. EXISTING GROUND ELEVATIONS BASED ON 1992 SITE FLYOVER.
2. ELEVATIONS ARE IN FEET ABOVE SEA LEVEL DATUM. (NOTE: "SEA LEVEL DATUM" REFERS TO THE NATIONAL GEODETIC VERTICAL DATUM [NGVD].)
3. PIPE EMBEDMENT ALONG SECTION OF SOLID PIPE IN HORIZONTAL MONITORING WELL SHALL BE CONSTRUCTED WITH SOIL BENTONITE PLUGS LOCATED 50 FEET ON CENTER.
4. HORIZONTAL MONITORING WELLS ARE NOT SHOWN ON OSDF GRADING DRAWINGS G-5 TO G-11.
5. FRAME AND ACCESS COVERS SHALL BE IN ACCORDANCE WITH SECTION 15000 OF THE OSDF SPECIFICATIONS.
6. PIPES AND FITTINGS SHALL BE IN ACCORDANCE WITH SECTION 02605 OF THE 15000 OF THE OSDF SPECIFICATIONS.
7. TRENCHING AND BACKFILLING SHALL BE IN ACCORDANCE WITH SECTION OF THE 02215 OF THE OSDF SPECIFICATIONS.
8. CONSTRUCTION CONTROL POINTS ARE PROVIDED ON DRAWING G-38. THE "+" SYMBOL REPRESENTS THE APPROPRIATE MANHOLE NUMBER FOR EACH CELL. CONSTRUCTION CONTROL POINTS REFER TO BOTTOM OF PIPE.

FOR INFORMATION ONLY

REV. NO.	DATE	DESCRIPTION	DES BY	DR BY	CHK BY	RVW BY	APP BY
G	11.10.96	FINAL SUBMITTAL TO EPA	DLVL	UMW	LA	KWC	RB
F	25.06.96	PREFINAL SUBMITTAL TO EPA					

SCALE AS SHOWN

OWNER/FACILITY:
UNITED STATES DEPARTMENT OF ENERGY
FERNALD ENVIRONMENTAL MANAGEMENT PROJECT

CLIENT:
FERNALD ENVIRONMENTAL RESTORATION MANAGEMENT CORPORATION

PROJECT:
ON-SITE DISPOSAL FACILITY 482

TITLE:
HORIZONTAL MONITORING WELL DETAILS
24D017_26

THIS DRAWING MAY NOT BE ISSUED FOR PROJECT TENDER OR CONSTRUCTION, UNLESS SEALED.

STATE OF OHIO — RUDOLPH BONAPARTE — E-56679 — REGISTERED PROFESSIONAL ENGINEER — SEAL

Rudolph Bonaparte SIGNATURE
8 Oct 1996 DATE

GeoSyntec Consultants
1100 LAKE HEARN DRIVE
ATLANTA, GEORGIA 30342 USA

FERMCO PROJECT NO.:	20100
FERMCO SUBCONTRACT NO.:	95PS005028
FERMCO DRAWING NO.:	90X-6000-G-001707
GEOSYNTEC PROJECT NO.:	GE3900-13.1
GEOSYNTEC DOCUMENT NO.:	F96-G166
SHEET NO.:	G-40
REVISION NO.:	G

FINAL DESIGN PACKAGE

M:\AACAD2C\GE3900 - 13\F96-G166 Wed Oct 09 10:33:05 1996 FERMCO\DWN



72 / - DETAIL
LDS AND LCS MANHOLES CONTROL SCHEMATIC
SCALE: NTS



74 / - DETAIL
LDS AND LCS MANHOLE SINGLE LINE DIAGRAM
SCALE: NTS

RELAY NUMBER - *Y1 : LDS-M* HI-HI LEVEL			
COIL L 12 VDC N	NORMALLY OPEN	NORMALLY CLOSED	CONTACT FUNCTION
CONTACTS #	NO	NC	
1 - 2	X		ENERGIZE (*TY4) ALARM LIGHT TIMER
NOTES: 1. RELAY SHOWN IN DE-ENERGIZED SHELF STATE			

RELAY NUMBER - *Y2 : LCS-M* HI-HI LEVEL			
COIL L 12 VDC N	NORMALLY OPEN	NORMALLY CLOSED	CONTACT FUNCTION
CONTACTS #	NO	NC	
1 - 2	X		ENERGIZE (*TY4) ALARM LIGHT TIMER
NOTES: 1. RELAY SHOWN IN DE-ENERGIZED SHELF STATE			

RELAY NUMBER - *Y3 : LDS-M*, LCS-M* ALARM LIGHT ENERGIZED			
COIL L 12 VDC N	NORMALLY OPEN	NORMALLY CLOSED	CONTACT FUNCTION
CONTACTS #	NO	NC	
1 - 2	X		ALARM LIGHT (LA-*01) ON
NOTES: 1. RELAY SHOWN IN DE-ENERGIZED SHELF STATE			

RELAY NUMBER - *TY4 : LDS-M*, LCS-M* ALARM LIGHT TIMER			
COIL L 12 VDC N	NORMALLY OPEN	NORMALLY CLOSED	CONTACT FUNCTION
CONTACTS #	NO	NC	
1 - 2	X		ACTIVATE ALARM LIGHT TIMER ENERGIZE (*Y3) ALARM LIGHT
NOTES: 1. RELAY SHOWN IN DE-ENERGIZED SHELF STATE			

73 / - DETAIL
LDS AND LCS MANHOLE CONTROL RELAY CONTACT CONFIGURATION
SCALE: NTS



57 / - DETAIL
LDS AND LCS MANHOLES ELECTRIC SERVICE PANEL AND POLE
SCALE: NTS
XREF: F96X0506



72A / - DETAIL
LDS AND LCS MANHOLES LEVEL INSTRUMENTATION LOOP DIAGRAM
SCALE: NTS
XREF: F96X0505

NOTES:

1. THE "*" SYMBOL REPRESENTS THE APPROPRIATE MANHOLE NUMBER FOR EACH CELL.
2. SETPOINT SHALL BE ADJUSTED IN ACCORDANCE WITH THE SYSTEMS PLAN.
3. MECHANICAL AND ELECTRICAL CONSTRUCTION SHALL BE IN ACCORDANCE WITH DIVISIONS 15 AND 16 OF THE LEACHATE CONVEYANCE SYSTEM SPECIFICATIONS.
4. SUPPORT RACK SHALL BE IN ACCORDANCE WITH SECTION 16100 OF THE OSDF SPECIFICATIONS.

FOR INFORMATION ONLY

REV. NO.	DATE	DESCRIPTION	DES BY	DR BY	CHK BY	RVW BY	APP BY
G	11.10.96	FINAL SUBMITTAL TO EPA	LF	BD	BJ	KWC	RB
F	25.06.96	PREFINAL SUBMITTAL TO EPA					

SCALE AS SHOWN

OWNER/FACILITY:
UNITED STATES DEPARTMENT OF ENERGY
FERNALD ENVIRONMENTAL MANAGEMENT PROJECT

CLIENT:

FERMCO Fernald Environmental Restoration Management Corporation

PROJECT:
ON-SITE DISPOSAL FACILITY 483

TITLE:
LEACHATE TRANSMISSION SYSTEM
ELECTRICAL DETAILS I
24007-23

THIS DRAWING MAY NOT BE ISSUED FOR PROJECT TENDER OR CONSTRUCTION, UNLESS SEALED.

Rudolph Bonaparte
SIGNATURE
8 Oct 1996
DATE

STATE OF OHIO
RUDOLPH BONAPARTE
E-56679
REGISTERED PROFESSIONAL ENGINEER

GeoSyntec Consultants
1100 LAKE HEARN DRIVE
ATLANTA, GEORGIA 30342 USA

FERMCO PROJECT NO.:	20100
FERMCO SUBCONTRACT NO.:	95PS005028
FERMCO DRAWING NO.:	90X-6000-E-00060
GEOSYNTEC PROJECT NO.:	GE3900-14.1
GEOSYNTEC DOCUMENT NO.:	F96-G126
SHEET NO.:	E-4
REVISION NO.:	G

FINAL DESIGN PACKAGE

M:\GACAD2CE\GE3900-14\DWG\F96-G126 Mon Oct 07 10:29:34 1996 John C.



78A / - DETAIL
PERMANENT LIFT STATION CONTROL PANEL
(NOTE 1)
SCALE: NTS



RELAY NUMBER – 10Y1 : PERMANENT LIFT STATION HI-HI LEVEL

COIL L 12 VDC N	NORMALLY OPEN	NORMALLY CLOSED	CONTACT FUNCTION
CONTACTS #	NO	NC	
1 – 2	X		ENERGIZE (10TY4) ALARM TIMER
3 – 4		X	MOTOR OPERATED VALVE (V-001) CLOSE

NOTE:
1. RELAY SHOWN IN DE-ENERGIZED SHELF STATE

RELAY NUMBER – 10Y2 : PERMANENT LIFT STATION ALARMS ON

COIL L 12 VDC N	NORMALLY OPEN	NORMALLY CLOSED	CONTACT FUNCTION
CONTACTS #	NO	NC	
1 – 2	X		ALARM LIGHT (LA-110) AND 12 VDC ALARM SIREN (LA-111B) ON
3 – 4	X		120 VAC ALARM SIREN (LA-111A) ON

NOTE:
1. RELAY SHOWN IN DE-ENERGIZED SHELF STATE

RELAY NUMBER – 10Y3 : PERMANENT LIFT STATION ANNULAR SPACE HI-LEVEL

COIL L 12 VDC N	NORMALLY OPEN	NORMALLY CLOSED	CONTACT FUNCTION
CONTACTS #	NO	NC	
1 – 2	X		ENERGIZE (10TY4) ALARM TIMER
3 – 4		X	MOTOR OPERATED VALVE (V-001) CLOSE

NOTE:
1. RELAY SHOWN IN DE-ENERGIZED SHELF STATE

RELAY NUMBER – 10TY4: PERMANENT LIFT STATION ALARM TIMER

COIL L 12 VDC N	NORMALLY OPEN	NORMALLY CLOSED	CONTACT FUNCTION
CONTACTS #	NO	NC	
1 – 2	X		ENERGIZE (10Y2) ALARM LIGHT AND SIREN

NOTE:
1. RELAY SHOWN IN DE-ENERGIZED SHELF STATE

RELAY NUMBER – 10Y5: PERMANENT LIFT STATION LOSS OF 120 VAC POWER

COIL L 120 VAC N	NORMALLY OPEN	NORMALLY CLOSED	CONTACT FUNCTION
CONTACTS #	NO	NC	
1 – 2	X		NORMAL 12 VDC HOT LEG
3 – 4	X		NORMAL 12 VDC COMMON
5 – 6		X	BATTERY 12 VDC COMMON
7 – 8		X	BATTERY 12 VDC HOT LEG
9 – 10		X	ENERGIZE (10TY4) ALARM TIMER

NOTE:
1. RELAY SHOWN IN DE-ENERGIZED SHELF STATE

RELAY NUMBER – 10Y6: PERMANENT LIFT STATION NORMAL 12 VDC POWER FUSE BLOWN

COIL L 12 VDC N	NORMALLY OPEN	NORMALLY CLOSED	CONTACT FUNCTION
CONTACTS #	NO	NC	
1 – 2		X	BATTERY 12 VDC COMMON
3 – 4		X	BATTERY 12 VDC HOT LEG
5 – 6		X	ENERGIZE (10TY4) ALARM TIMER
7 – 8	X		BLOWN FUSE LATCH

NOTE:
1. RELAY SHOWN IN DE-ENERGIZED SHELF STATE

79 / - DETAIL
PERMANENT LIFT STATION CONTROL RELAY CONTACT CONFIGURATION
SCALE: NTS



80 / - DETAIL
PERMANENT LIFT STATION LEVEL INSTRUMENTATION
LOOP DIAGRAM FOR LOOP L-110
SCALE: NTS

62 / S-3 DETAIL
LIGHT FIXTURE FOR POLE OP 82
(NOTE 3)
SCALE: NTS



78 / - DETAIL
PERMANENT LIFT STATION CONTROL SCHEMATIC
SCALE: NTS

NOTES:

1. REFER TO DRAWING E-00325 FOR PANEL LOCATION ON EQUIPMENT RACK.
2. REFER TO DRAWING E-00324 FOR DISTRIBUTION PANEL DETAILS.
3. REFER TO DRAWINGS E-00500 AND E-00501 FOR POLE LOCATION AND ELECTRIC POWER DETAILS.
4. FURNISH OUTDOOR AREA DIE CAST ALUMINUM LIGHTING FIXTURE WITH 70-WATT HIGH PRESSURE SODIUM LAMP. BALLAST WIRED FOR 110 VAC. PHOTOCELL CONTROL FOR DUSK TO DAWN OPERATION. GLASS REFRACTOR LENS. POLE-MOUNTED ON 2 FOOT ALUMINUM ARM. FURNISH COMPLETE WITH FIXTURE, LAMP, ARM, HOOK-UP WIRE, PHOTO CONTROL AND MOUNTING HARDWARE.

FINAL DESIGN PACKAGE

FOR INFORMATION ONLY

REV. NO.	DATE	DESCRIPTION	DES BY	DR BY	CHK BY	RVW BY	APP BY
G	11.10.96	FINAL SUBMITTAL TO EPA	LF	RD	BJ	KWC	RB
F	25.06.96	PREFINAL SUBMITTAL TO EPA					

SCALE AS SHOWN

OWNER/FACILITY:
UNITED STATES DEPARTMENT OF ENERGY
FERNALD ENVIRONMENTAL MANAGEMENT PROJECT

CLIENT:
FERNALD ENVIRONMENTAL RESTORATION MANAGEMENT CORPORATION

PROJECT:
ON-SITE DISPOSAL FACILITY 434

TITLE:
LEACHATE TRANSMISSION SYSTEM
ELECTRICAL DETAILS IV
240017-29

THIS DRAWING MAY NOT BE ISSUED FOR PROJECT TENDER OR CONSTRUCTION, UNLESS SEALED.

Rudolph Bonaparte
SIGNATURE
8 Oct 1996
DATE

STATE OF OHIO
RUDOLPH BONAPARTE
E-56679
REGISTERED PROFESSIONAL ENGINEER

GeoSyntec Consultants
1100 LAKE HEARN DRIVE
ATLANTA, GEORGIA 30342 USA

FERMCO PROJECT NO.:	20100
FERMCO SUBCONTRACT NO.:	95PS005028
FERMCO DRAWING NO.:	90X-5000-E-00061
GEOSYNTEC PROJECT NO.:	GE3900-13.1
GEOSYNTEC DOCUMENT NO.:	F96-G158
SHEET NO.:	E-7
REVISION NO.:	G

M:\GACAD2\GE3900-~13\F96-G158 Mon Oct 07 18:15:10 1996 PULU

452



84 / M-2 DETAIL
LCS AND LDS MANHOLE ALARM CONTROL PANEL
(NOTE 4)
SCALE: NTS



86 / - DETAIL
PIPING AND INSTRUMENTATION DIAGRAM POST CLOSURE
SCALE: NTS

PIPING CODES

MC - PS - MT - LN

- MC = FLOW MEDIUM CODE
- PS = NOMINAL PIPE SIZE (CARRIER/CONTAINMENT)
- MT = PIPE MATERIAL STANDARD ABBREVIATION
- LN = PIPELINE NUMBER

EXAMPLE: WW-6"/10"-B4-0006

- WW = WASTEWATER
- 6"/10" = 6"/10" NOMINAL PIPE SIZE (CARRIER/CONTAINMENT)
- B4 = HDPE
- 0006 = PIPELINE NUMBER 0006

STANDARD ABBREVIATIONS

A	A53, GRADE A SEAMLESS STEEL PIPE
AWG	AMERICAN WIRE GAUGE
B4	HIGH DENSITY POLYETHYLENE
GPM	GALLONS PER MINUTE
HDPE	HIGH DENSITY POLYETHYLENE
mA	MILLIAMP
SDR	STANDARD DIMENSION RATIO
T1	TYPE 316L, STAINLESS STEEL PIPE
WW	WASTEWATER

EQUIPMENT ABBREVIATIONS

FM	FORCEMAIN
LA	ALARM LIGHT
LIC	PROGRAMMABLE LEVEL INDICATOR/CONTROLLER
LT	LEVEL TRANSMITTER
P	CONTROL PANEL
PC	PRIMARY CONTAINMENT VESSEL
QC	QUICK CONNECT
PMP	SUBMERSIBLE PUMP
V	VALVE

INSTRUMENT CODES

AAA - BCC

- AAA = EQUIPMENT ABBREVIATION
- B = CELL NUMBER
- CC = INSTRUMENT NUMBER

EXAMPLE: V-304

- V = VALVE
- 3 = CELL 3
- 04 = INSTRUMENT NUMBER 04

SYMBOLS

- BALL VALVE
- BLIND FLANGE
- BUTTERFLY VALVE (CLOSED POSITION)
- BUTTERFLY VALVE (OPEN POSITION)
- CHECK VALVE
- ELECTRICAL CONTROL PANEL
- ELECTRICAL SIGNAL
- FLOW DIRECTION
- LOCAL MOUNTED INSTRUMENT
- MATERIAL CODE BREAK
- MONITORING PORT (WITH VALVE) (NOTE 2)
- MOTOR OPERATOR
- OPEN PIPE END
- PIPE SIZE BREAK
- QUICK CONNECT
- SAMPLING PORT (WITH VALVE) (NOTE 2)
- SUBMERSIBLE PUMP
- VENT WITH SCREEN
- PRESSURE INDICATOR

FINAL DESIGN PACKAGE

NOTES:

1. SUBCONTRACTOR SHALL MANAGE THE LEACHATE TRANSMISSION SYSTEM IN ACCORDANCE WITH ALL APPLICABLE SECTIONS OF THE OSDF SPECIFICATIONS AND THE OSDF SYSTEMS PLAN.
2. MONITORING PORT IS LOCATED ON 10-INCH CONTAINMENT PIPE. SAMPLING PORT IS LOCATED ON 6-INCH CARRIER PIPE.
3. PUMP SUCTION AND DISCHARGE CONNECTIONS SHALL BE USED TO CONVEY LIQUID FROM THE PRIMARY CONTAINMENT VESSEL TO THE LEACHATE TRANSMISSION SYSTEM PIPE:
   LINE NUMBERS WW-2"-B4-*005: SUCTION
   LINE NUMBERS WW-2"-B4-*006: DISCHARGE
4. THE "*" SYMBOL REPRESENTS THE APPROPRIATE MANHOLE NUMBER FOR EACH CELL.
5. SEE SEPARATE DESIGN PACKAGE FOR THE DESIGN OF VALVES V-002 THROUGH V-005, THE PERMANENT LIFT STATION PUMPS, AND THE FORCEMAIN (LEACHATE TRANSMISSION SYSTEM CONNECTOR) TO THE BIODENITRIFICATION SURGE LAGOON.

REV. NO.	DATE	DESCRIPTION	DES BY	DR BY	CHK BY	RVW BY	APP BY
G	11.10.96	FINAL SUBMITTAL TO EPA	BJ	RD	LA/DS	KWC	RB
F	25.06.96	PREFINAL SUBMITTAL TO EPA					

SCALE AS SHOWN

FOR INFORMATION ONLY

OWNER/FACILITY:
UNITED STATES DEPARTMENT OF ENERGY
FERNALD ENVIRONMENTAL MANAGEMENT PROJECT

CLIENT:
FERMCO — FERNALD ENVIRONMENTAL RESTORATION MANAGEMENT CORPORATION

PROJECT:
ON-SITE DISPOSAL FACILITY 485

TITLE:
LEACHATE TRANSMISSION SYSTEM PIPING AND INSTRUMENTATION DIAGRAM
24007-30

THIS DRAWING MAY NOT BE ISSUED FOR PROJECT TENDER OR CONSTRUCTION, UNLESS SEALED.

Rudolph Bonaparte
SIGNATURE
8 Oct 1996
DATE

STATE OF OHIO — RUDOLPH BONAPARTE — E-56679 — REGISTERED PROFESSIONAL ENGINEER — SEAL

GeoSyntec Consultants
1100 LAKE HEARN DRIVE
ATLANTA, GEORGIA 30342 USA

FERMCO PROJECT NO.:	20100
FERMCO SUBCONTRACT NO.:	95PS005028
FERMCO DRAWING NO.:	90X-6000-M-00048
GEOSYNTEC PROJECT NO.:	GE3900-13.1
GEOSYNTEC DOCUMENT NO.:	F96-G043
SHEET NO.:	M-2
REVISION NO.:	G

M:\GACAD02\GE3900-13\F96-G043 Tue Oct 08 07:23:11 1996 PULU WALKER



93 G-5 **SECTIONAL PLAN**
LDS AND LCS MANHOLES AT CELL 1
(NOTES 1 AND 5)
SCALE: 1" = 2'
XREF: F96X0273

SECTION (TYPICAL)
LDS MANHOLE AT CELLS 1 THROUGH 9
(NOTE 8)
SCALE: 1" = 2'
XREF: F96X0084



B M-4 **SECTION (TYPICAL)**
LCS AND LDS MANHOLES AT CELLS 1 THROUGH 9
(NOTE 6)
SCALE: 1" = 2'
XREF: F96X0297



C M-4 **SECTION**
LCS MANHOLE AT CELL 1
SCALE: 1" = 2'
XREF: F96X0298

NOTES:

1. MANHOLES, PIPES, AND FITTINGS SHALL BE IN ACCORDANCE WITH SECTION 02605 OF THE OSDF SPECIFICATIONS.
2. FRAME AND ACCESS COVERS, VALVES, LEACHATE TRANSMISSION SYSTEM VENT PIPE, AND LEACHATE TRANSMISSION SYSTEM VENT PIPE SUPPORT SHALL BE IN ACCORDANCE WITH SECTION 15000 OF THE OSDF SPECIFICATIONS.
3. TRENCHING AND BACKFILLING SHALL BE IN ACCORDANCE WITH SECTION 02215 OF THE OSDF SPECIFICATIONS.
4. DETAILS ARE SHOWN TO SCALE AS NOTED EXCEPT FOR THE GEOSYNTHETICS WHICH ARE SHOWN AT AN EXAGGERATED SCALE FOR CLARITY. MATERIAL TOLERANCES SHALL BE WITHIN THE LIMITS GIVEN IN THE OSDF SPECIFICATIONS.
5. PIPE CENTRALIZERS ARE NOT SHOWN IN THIS PLAN.
6. FINISHED GRADES ARE NOT SHOWN IN THIS SECTION.
7. CONSTRUCTION CONTROL POINT TABLES ARE PROVIDED ON DRAWING G-38. THE "+" SYMBOL REPRESENTS THE APPROPRIATE MANHOLE NUMBER FOR EACH CELL.
8. PRIMARY CONTAINMENT VESSEL IS NOT SHOWN IN THIS SECTION.
9. FIXED END SEAL ON LTS PIPE SHALL BE PERFORATED WITH 6X5/8-INCH-DIAMETER HOLES EVENLY SPACED AT 60 DEGREES APART.

FOR INFORMATION ONLY

REV. NO.	DATE	DESCRIPTION	DES BY	DR BY	CHK BY	RVW BY	APP BY
G	11.10.96	FINAL SUBMITTAL TO EPA	BJ	AF	LA	KWC	RB
F	25.06.96	PREFINAL SUBMITTAL TO EPA					

SCALE AS SHOWN

OWNER/FACILITY:
UNITED STATES DEPARTMENT OF ENERGY
FERNALD ENVIRONMENTAL MANAGEMENT PROJECT

CLIENT:
Fernald Environmental Restoration Management Corporation
FERNALD ENVIRONMENTAL RESTORATION MANAGEMENT CORPORATION

PROJECT:
ON-SITE DISPOSAL FACILITY 486

TITLE:
LEACHATE TRANSMISSION SYSTEM GRAVITY LINE AND MANHOLE MECHANICAL DETAILS I
24017-31

THIS DRAWING MAY NOT BE ISSUED FOR PROJECT TENDER OR CONSTRUCTION, UNLESS SEALED.

Rudolph Bonaparte
SIGNATURE
8 Oct 1996
DATE

STATE OF OHIO
RUDOLPH BONAPARTE
E-56679
REGISTERED PROFESSIONAL ENGINEER
SEAL

GeoSyntec Consultants
1100 LAKE HEARN DRIVE
ATLANTA, GEORGIA 30342 USA

FERMCO PROJECT NO.:	20100
FERMCO SUBCONTRACT NO.:	95PS005028
FERMCO DRAWING NO.:	90X-6000-M-00049
GEOSYNTEC PROJECT NO.:	GE3900-13.1
GEOSYNTEC DOCUMENT NO.:	F96-G056
SHEET NO.:	M-4
REVISION NO.:	G

FINAL DESIGN PACKAGE

Wed Oct 09 16:37:32 1996 J MILLER

452



94 G-5 **SECTIONAL PLAN**
LDS AND LCS MANHOLES AT CELLS 2 THROUGH 9
(NOTES 1 AND 6)
SCALE: 1" = 2'
XREF: F96X0104



B M-5 **SECTION (TYPICAL)**
LCS MANHOLE AT CELLS 1 THROUGH 9
SCALE: 1" = 2'
XREF: F96X0091



C M-5 **SECTION**
LCS MANHOLE AT CELLS 2 THROUGH 9
SCALE: 1" = 2'
XREF: F96X0091

101 - **DETAIL**
CLEANOUT AND AUXILIARY CONNECTION
(NOTE 2)
SCALE: 1" = 2'
XREF: F96X0477



A M-5 **SECTION (TYPICAL)**
LCS MANHOLE AT CELLS 1 THROUGH 9
(NOTE 6)
SCALE: 1" = 2'
XREF: F96X0234

NOTES:

1. MANHOLES, PIPES, AND FITTINGS SHALL BE IN ACCORDANCE WITH SECTION 02605 OF THE OSDF SPECIFICATIONS.
2. FRAME AND ACCESS COVERS, VALVES, AND AUXILIARY CONNECTION TO LEACHATE TRANSMISSION SYSTEM SHALL BE IN ACCORDANCE WITH SECTION 15000 OF THE OSDF SPECIFICATIONS. AUXILIARY CONNECTION TO LTS CLEANOUTS SHALL BE INSTALLED IN ACCORDANCE WITH THE SYSTEMS PLAN OR AT THE DIRECTION OF THE CONSTRUCTION MANAGER.
3. TRENCHING AND BACKFILLING SHALL BE IN ACCORDANCE WITH SECTION 02215 OF THE OSDF SPECIFICATIONS.
4. DETAILS ARE SHOWN TO SCALE AS NOTED EXCEPT FOR THE GEOSYNTHETICS WHICH ARE SHOWN AT AN EXAGGERATED SCALE FOR CLARITY. MATERIAL TOLERANCES SHALL BE WITHIN THE LIMITS GIVEN IN THE OSDF SPECIFICATIONS.
5. PIPE CENTRALIZERS ARE NOT SHOWN IN THIS PLAN.
6. FINISHED GRADES ARE NOT SHOWN IN THIS SECTION.
7. CONSTRUCTION CONTROL POINT TABLES ARE PROVIDED ON DRAWING G-38. THE "+" SYMBOL REPRESENTS THE APPROPRIATE MANHOLE NUMBER FOR EACH CELL.

FOR INFORMATION ONLY

REV. NO.	DATE	DESCRIPTION	DES. BY	DR. BY	CHK. BY	RVW BY	APP. BY
C	11.10.96	FINAL SUBMITTAL TO EPA	BJ	JRM	LA/DS	KWC	RB
F	25.06.96	PREFINAL SUBMITTAL TO EPA					

SCALE AS SHOWN

OWNER/FACILITY:
UNITED STATES DEPARTMENT OF ENERGY
FERNALD ENVIRONMENTAL MANAGEMENT PROJECT

CLIENT:
FERMCO FERNALD ENVIRONMENTAL RESTORATION MANAGEMENT CORPORATION
Fernald Environmental Restoration Management Corporation

PROJECT:
ON-SITE DISPOSAL FACILITY 487

TITLE:
LEACHATE TRANSMISSION SYSTEM GRAVITY LINE AND MANHOLE MECHANICAL DETAILS II
240017-32

THIS DRAWING MAY NOT BE ISSUED FOR PROJECT TENDER OR CONSTRUCTION, UNLESS SEALED.

Rudolph Bonaparte
SIGNATURE
8 Oct 1996
DATE

STATE OF OHIO
RUDOLPH BONAPARTE
E-56679
REGISTERED PROFESSIONAL ENGINEER
SEAL

GeoSyntec Consultants
1100 LAKE HEARN DRIVE
ATLANTA, GEORGIA 30342 USA

FERMCO PROJECT NO.:	20100
FERMCO SUBCONTRACT NO.:	95PS005028
FERMCO DRAWING NO.:	90X-6000-M-00050
GEOSYNTEC PROJECT NO.:	GE3900-13.1
GEOSYNTEC DOCUMENT NO.:	F96-G057
SHEET NO.:	M-5
REVISION NO.:	G

FINAL DESIGN PACKAGE

M:\ACAD\DOCS\GE3900\F-_13\F96-G057 Wed Oct 09 10:10:37 1996 FERMCO\DMN



96 M-4 SECTIONAL PLAN
PRIMARY CONTAINMENT VESSEL
SCALE: 1" = 6"
XREF: F9641358



100 M-4 DETAIL
LEVEL TRANSMITTER PIPE
SCALE: NTS
XREF: F9650279



100A M-6 DETAIL
PERFORATED PIPE
SCALE: 1" = 3"
XREF: F9640279



98 G-18 DETAIL
PIPE EMBEDMENT
(NOTE 3)
SCALE: 1" = 1'
XREF: F9630446



A M-6A SECTION
LDS OUTLET PIPE
SCALE: 1" = 6"
XREF: F9641358



B M-6 SECTION
PRIMARY CONTAINMENT VESSEL
(NOTE 4)
SCALE: 1" = 6"
XREF: F9641358



C M-6 DETAIL
PIPE EMBEDMENT
(NOTE 3)
SCALE: 1" = 1'
XREF: F9640126



D M-6 DETAIL
PIPE EMBEDMENT AT
SOIL-BENTONITE PLUG
(NOTE 3)
SCALE: 1" = 1'
XREF: F9640126



101A M-5 DETAIL
AUXILIARY CONNECTION
SCALE: 1" = 6"
XREF: F9641287



102 M-4 DETAIL
MONITORING PORT
SCALE: 1" = 6"
XREF: F9641238



103 M-5 DETAIL
SAMPLING AND MONITORING PORTS
SCALE: 1" = 6"
XREF: F9641238



97 M-4 DETAIL
PIPE SUPPORT
SCALE: 1" = 6"
XREF: F9640087



99 M-4 DETAIL
TRANSITIONAL FLANGE
SCALE: 1" = 6"
XREF: F9640278

NOTES:

1. PIPES, PIPE SUPPORTS, AND FITTINGS SHALL BE IN ACCORDANCE WITH SECTION 02605 THE OSDF SPECIFICATIONS. PIPE CRADLE SHALL NOT BE WELDED TO PIPE WHICH SUPPORTS.
2. UNLESS OTHERWISE NOTED, SOIL-BENTONITE PLUG SHALL BE CONSTRUCTED AT 150 FOOT INTERVAL ALONG THE PIPE EMBEDMENT FILL LAYER, IN ACCORDANCE WITH SECTION 02215 OF THE OSDF SPECIFICATIONS.
3. TRENCHING AND BACKFILLING SHALL BE IN ACCORDANCE WITH SECTION 02215 OF THE OSDF SPECIFICATIONS.
4. LEACHATE DETECTION SYSTEM OUTLET PIPE IS NOT SHOWN IN THIS SECTION.

FOR INFORMATION ONLY

REV. NO.	DATE	DESCRIPTION	DES BY	DR BY	CHK BY	RVW BY	APP BY
G	11.10.96	FINAL SUBMITTAL TO EPA	BJ	RD	LA/DS	KWC	RB
F	25.06.96	PREFINAL SUBMITTAL TO EPA					

SCALE AS SHOWN

OWNER/FACILITY:
UNITED STATES DEPARTMENT OF ENERGY
FERNALD ENVIRONMENTAL MANAGEMENT PROJECT

CLIENT:
FERMCO Fluor Environmental Restoration Management Corporation
FERNALD ENVIRONMENTAL RESTORATION MANAGEMENT CORPORATION

PROJECT:
ON-SITE DISPOSAL FACILITY 488

TITLE:
LEACHATE TRANSMISSION SYSTEM GRAVITY LINE AND MANHOLE MECHANICAL DETAILS III
24007-33

THIS DRAWING MAY NOT BE ISSUED FOR PROJECT TENDER OR CONSTRUCTION, UNLESS SEALED.

Rudolph Bonaparte
SIGNATURE
8 Oct 1996
DATE

STATE OF OHIO
RUDOLPH BONAPARTE
E-56679
REGISTERED PROFESSIONAL ENGINEER

GeoSyntec Consultants
1100 LAKE HEARN DRIVE
ATLANTA, GEORGIA 30342 USA

FERMCO PROJECT NO.:	20100
FERMCO SUBCONTRACT NO.:	95P5005028
FERMCO DRAWING NO.:	90-X-6000-M-00051
GEOSYNTEC PROJECT NO.:	GE3900-13.1
GEOSYNTEC DOCUMENT NO.:	F96-G058
SHEET NO.:	M-6
REVISION NO.:	G

FINAL DESIGN PACKAGE

H:\F96-G058 Tue Oct 08 08:48:30 1996 J MILLER



108 / - SECTIONAL PLAN
PERMANENT LIFT STATION
(NOTES 1 AND 7)
SCALE: 1" = 2'



A M-9 SECTION
PERMANENT LIFT STATION
(NOTES 1 AND 5)
SCALE: 1" = 2'



B M-9 SECTION
PERMANENT LIFT STATION
(NOTE 6)
SCALE: 1" = 2'

NOTES:

1. PRIMARY CONTAINMENT, SECONDARY CONTAINMENT, PIPES, AND FITTINGS SHALL BE IN ACCORDANCE WITH SECTION 02605 OF THE OSDF SPECIFICATIONS.
2. FRAME, ACCESS COVERS, AND VALVES SHALL BE IN ACCORDANCE WITH SECTION 15000 OF THE OSDF SPECIFICATIONS.
3. TRENCHING AND BACKFILLING SHALL BE IN ACCORDANCE WITH SECTION 02215 OF THE OSDF SPECIFICATIONS.
4. STIFFENER RINGS AROUND PRIMARY CONTAINMENT SHALL BE NOTCHED TO ALLOW LIQUID FLOW TO THE LEVEL TRANSMITTER PIPE.
5. SEE SEPARATE DESIGN PACKAGE FOR DESIGN OF SUBMERSIBLE PUMPS, PUMP VALVES, PERMANENT LIFT STATION PUMP ELECTRICAL DETAILS, AND FORCEMAIN TO BIODENITRIFICATION SURGE LAGOON.
6. DETAILS ARE SHOWN TO SCALE AS NOTED EXCEPT FOR THE GEOSYNTHETICS WHICH ARE SHOWN AT AN EXAGGERATED SCALE FOR CLARITY. MATERIAL TOLERANCES SHALL BE WITHIN THE LIMITS GIVEN IN THE OSDF SPECIFICATIONS.
7. PIPE CENTRALIZERS ARE NOT SHOWN IN THIS PLAN.
8. LEVEL TRANSMITTER PIPE IS SHOWN IN THIS SECTION FOR CLARITY.
9. CONSTRUCTION CONTROL POINTS TABLES ARE PROVIDED ON DRAWING G-38.

FOR INFORMATION ONLY

REV. NO.	DATE	DESCRIPTION	DES BY	DR BY	CHK BY	RVW BY	APP BY
G	11.10.96	FINAL SUBMITTAL TO EPA	BJ	JRM	LA	KWC	RB
F	25.06.96	PREFINAL SUBMITTAL TO EPA					

SCALE AS SHOWN

OWNER/FACILITY:
UNITED STATES DEPARTMENT OF ENERGY
FERNALD ENVIRONMENTAL MANAGEMENT PROJECT

CLIENT:
FERMCO FERNALD ENVIRONMENTAL RESTORATION MANAGEMENT CORPORATION

PROJECT:
ON-SITE DISPOSAL FACILITY 489

TITLE:
LEACHATE TRANSMISSION SYSTEM
LIFT STATION MECHANICAL DETAILS III

240017-34

THIS DRAWING MAY NOT BE ISSUED FOR PROJECT TENDER OR CONSTRUCTION, UNLESS SEALED.

Rudolph Bonaparte
SIGNATURE
8 Oct 1996
DATE

STATE OF OHIO
RUDOLPH BONAPARTE
E-56679
REGISTERED PROFESSIONAL ENGINEER
SEAL

GeoSyntec Consultants
1100 LAKE HEARN DRIVE
ATLANTA, GEORGIA 30342 USA

FERMCO PROJECT NO.:	20100
FERMCO SUBCONTRACT NO.:	95P5005028
FERMCO DRAWING NO.:	90X-6000-M-00052
GEOSYNTEC PROJECT NO.:	GE3900-13.1
GEOSYNTEC DOCUMENT NO.:	F96-0059
SHEET NO.:	M-9
REVISION NO.:	G

FINAL DESIGN PACKAGE

H:\F96-0059 Tue Oct 08 14:36:50 1996 J MILLER



109 G-11 PLAN
MANHOLE AND HORIZONTAL MONITORING WELL COVER SLAB
SCALE: 1" = 2'
XREF: F96H0300



110 M-4 SECTIONAL PLAN
MANHOLE AND HORIZONTAL MONITORING WELL COVER SLAB
(NOTE 5)
SCALE: 1" = 2'
XREF: F96H0301



112 M-4 SECTIONAL PLAN
MANHOLE ANTIFLOTATION ANCHOR
(NOTES 7 AND 8)
SCALE: 1" = 2'
XREF: F96H0614



A S-1 SECTION
MANHOLE COVER SLAB
(NOTES 2, 5, AND 6)
SCALE: 1" = 2'
XREF: F96H0355



B S-1 SECTION
MANHOLE BASE AND ANTIFLOTATION ANCHOR
SCALE: 1" = 2'
XREF: F96H0382

NOTES:

1. FRAME AND ACCESS COVER SHALL BE IN ACCORDANCE WITH SECTION 15000 OF THE OSDF SPECIFICATIONS.
2. MANHOLE COVER SUPPORTS, AND MANHOLE FLOOR SUPPORTS SHALL BE IN ACCORDANCE WITH SECTION 02605 OF THE OSDF SPECIFICATIONS.
3. TRENCHING AND BACKFILLING SHALL BE IN ACCORDANCE WITH SECTION 02215 OF THE OSDF SPECIFICATIONS.
4. ELECTRICAL CONDUIT PENETRATIONS INTO MANHOLES SHALL BE IN ACCORDANCE WITH SECTIONS 02605 AND 16110 OF THE OSDF SPECIFICATIONS.
5. MANHOLE HDPE COVER SHALL BE TEMPORARILY SHORED DURING CONSTRUCTION OF MANHOLE COVER SLAB IN ACCORDANCE WITH SECTION 03100 OF THE OSDF SPECIFICATIONS.
6. VERTICAL CONSTRUCTION JOINTS SHALL BE IN ACCORDANCE WITH SECTION 03100 OF THE OSDF SPECIFICATIONS.
7. MANHOLE FLOOR SUPPORTS ARE NOT SHOWN IN THIS PLAN.
8. SUBCONTRACTOR MAY PLACE CONCRETE AGAINST NATURAL GROUND WITH APPROVAL OF THE CONSTRUCTION MANAGER.
9. SEE SEPARATE DESIGN PACKAGE FOR THE DESIGN OF PERMANENT LIFT STATION PUMP AND ELECTRICAL DETAILS.
10. DETAILS ARE SHOWN TO SCALE AS NOTED EXCEPT FOR THE GEOSYNTHETICS WHICH ARE SHOWN AT AN EXAGGERATED SCALE FOR CLARITY. MATERIAL TOLERANCES SHALL BE WITHIN THE LIMITS GIVEN IN THE OSDF SPECIFICATIONS.
11. SUBCONTRACTOR SHALL INSTALL ELECTRICAL EQUIPMENT SUPPORTS IN ACCORDANCE WITH SECTION 16100 OF THE OSDF SPECIFICATIONS.

FOR INFORMATION ONLY

REV. NO.	DATE	DESCRIPTION	DES BY	DR BY	CHK BY	RVW BY	APP BY
G	11.10.96	FINAL SUBMITTAL TO EPA	DLVL	UMW	LA	KWC	RB
F	25.06.96	PREFINAL SUBMITTAL TO EPA					

SCALE AS SHOWN

OWNER/FACILITY:
UNITED STATES DEPARTMENT OF ENERGY
FERNALD ENVIRONMENTAL MANAGEMENT PROJECT

CLIENT:
FERNALD ENVIRONMENTAL RESTORATION MANAGEMENT CORPORATION

PROJECT:
ON-SITE DISPOSAL FACILITY 490

TITLE:
LEACHATE TRANSMISSION SYSTEM
STRUCTURAL DETAILS I
240017.35

THIS DRAWING MAY NOT BE ISSUED FOR PROJECT TENDER OR CONSTRUCTION, UNLESS SEALED.

Rudolph Bonaparte
SIGNATURE
8 Oct 1996
DATE

STATE OF OHIO
RUDOLPH BONAPARTE
E-56679
REGISTERED PROFESSIONAL ENGINEER
SEAL

GeoSyntec Consultants
1100 LAKE HEARN DRIVE
ATLANTA, GEORGIA 30342 USA

FERMCO PROJECT NO.:	20100
FERMCO SUBCONTRACT NO.:	95P5005028
FERMCO DRAWING NO.:	90X-6000-S-00053
GEOSYNTEC PROJECT NO.:	GE3900-13.1
GEOSYNTEC DOCUMENT NO.:	F96-G148
SHEET NO.:	S-1
REVISION NO.:	G

FINAL DESIGN PACKAGE

M:\GACADD\CVE3900\F-13\F96-G148 Tue Oct 08 13:45:20 1996 FERMCO\DUNN



116 G-2 **PLAN**
PERMANENT LIFT STATION
SCALE: 1" = 2'
XREF: F96I0206



117 M-9 **SECTIONAL PLAN**
PERMANENT LIFT STATION COVER SLAB
SCALE: 1" = 2'
XREF: F96I0445



83 S-1 **DETAIL**
BOLLARD
(NOTE 9)
SCALE: 1" = 2'
XREF: F96I0509



A S-3 **SECTION**
PERMANENT LIFT STATION
SCALE: 1" = 2'
XREF: F96I0453

NOTES:

1. FRAME AND ACCESS COVER SHALL BE IN ACCORDANCE WITH SECTION 15000 OF THE OSDF SPECIFICATIONS.
2. HDPE GUSSETS, MANHOLE COVER SUPPORTS, AND MANHOLE FLOOR SUPPORTS SHALL BE IN ACCORDANCE WITH SECTION 02605 OF THE OSDF SPECIFICATIONS.
3. TRENCHING AND BACKFILLING SHALL BE IN ACCORDANCE WITH SECTION 02215 OF THE OSDF SPECIFICATIONS.
4. ELECTRICAL CONDUIT PENETRATIONS INTO MANHOLES SHALL BE IN ACCORDANCE WITH SECTIONS 02605 AND 16110 OF THE OSDF SPECIFICATIONS.
5. MANHOLE HDPE COVER SHALL BE TEMPORARILY SHORED DURING CONSTRUCTION OF MANHOLE COVER SLAB IN ACCORDANCE WITH SECTION 03100 OF THE OSDF SPECIFICATIONS.
6. VERTICAL CONSTRUCTION JOINTS SHALL BE IN ACCORDANCE WITH SECTION 03100 OF THE OSDF SPECIFICATIONS.
7. SUBCONTRACTOR MAY PLACE CONCRETE AGAINST NATURAL GROUND WITH APPROVAL OF THE CONSTRUCTION MANAGER.
8. SEE SEPARATE DESIGN PACKAGE FOR THE DESIGN OF PERMANENT LIFT STATION PUMP AND ELECTRICAL DETAILS.
9. EXPOSED CONCRETE INCLUDING TOPS AND BASE OF BOLLARDS SHALL HAVE A 1-INCH CROWN TO PROMOTE DRAINAGE.

FOR INFORMATION ONLY

REV. NO.	DATE	DESCRIPTION	DES BY	DR BY	CHK BY	RVW BY	APP BY
G	11.10.96	FINAL SUBMITTAL TO EPA	DLVL	JRM	LA/DS	KWC	RB
F	25.06.96	PREFINAL SUBMITTAL TO EPA					

SCALE AS SHOWN

OWNER/FACILITY:
UNITED STATES DEPARTMENT OF ENERGY
FERNALD ENVIRONMENTAL MANAGEMENT PROJECT

CLIENT:
FERMCO FERNALD ENVIRONMENTAL RESTORATION MANAGEMENT CORPORATION

PROJECT:
ON-SITE DISPOSAL FACILITY 491

TITLE:
LEACHATE TRANSMISSION SYSTEM
STRUCTURAL DETAILS III
24007-36

THIS DRAWING MAY NOT BE ISSUED FOR PROJECT TENDER OR CONSTRUCTION, UNLESS SEALED.

STATE OF OHIO
RUDOLPH BONAPARTE
E-56679
REGISTERED PROFESSIONAL ENGINEER

Rudolph Bonaparte
SIGNATURE
8 Oct 1996
DATE

GeoSyntec Consultants
1100 LAKE HEARN DRIVE
ATLANTA, GEORGIA 30342 USA

FERMCO PROJECT NO.:	20100
FERMCO SUBCONTRACT NO.:	95PS005028
FERMCO DRAWING NO.:	90X-6000-S-00054
GEOSYNTEC PROJECT NO.:	GE3900-13.1
GEOSYNTEC DOCUMENT NO.:	F96-G155
SHEET NO.:	S-3
REVISION NO.:	G

FINAL DESIGN PACKAGE

H:\F96-G155 Wed Oct 09 12:50:23 1996 J MILLER

452



118 G-2 DETAIL
TWO-LEAF SWING GATE
SCALE: 1" = 2'
XREF: F96IG511



119 G-2 DETAIL
LINE POST CONNECTION TO END OR CORNER POST
SCALE: 1" = 2'
XREF: F96IG515



120 G-2 DETAIL
PULL POST
SCALE: 1" = 2'
XREF: F96IG513



121 - DETAIL
RIGHT-OF-WAY FENCE GROUND
SCALE: NTS
XREF: F96IG514

NOTES:

1. CHAIN LINK FENCE AND GATES SHALL BE IN ACCORDANCE WITH SECTION 02831 OF THE OSDF SPECIFICATIONS.
2. SUPPORTING ARMS SHALL SLOPE TO THE OUTSIDE OF THE FENCE AT 45 DEGREES FROM THE VERTICAL.
3. GATE POSTS SUPPORTING LEAF WIDTHS UP TO 6 FEET SHALL HAVE AN OUTSIDE DIAMETER OF 2 7/8 INCHES. GATE POSTS SUPPORTING LEAF WIDTHS GREATER THAN 6 FEET AND LESS THAN 13 FEET SHALL HAVE AN OUTSIDE DIAMETER OF 4 INCHES.
4. EXPOSED TOPS OF CONCRETE FOOTINGS SHALL HAVE A 1-INCH CROWN TO PROMOTE DRAINAGE.
5. SEE PLAN DRAWINGS FOR LOCATIONS OF CHAIN LINK FENCE AND GATES.
6. CHAIN LINK FENCE SHALL BE GROUNDED ON BOTH SIDES OF FENCE.

FOR INFORMATION ONLY

REV. NO.	DATE	DESCRIPTION	DES BY	DR BY	CHK BY	RVW BY	APP BY
G	11.10.96	FINAL SUBMITTAL TO EPA	DLVL	UMW	LA	KWC	RB
F	25.06.96	PREFINAL SUBMITTAL TO EPA					

OWNER/FACILITY:
UNITED STATES DEPARTMENT OF ENERGY
FERNALD ENVIRONMENTAL MANAGEMENT PROJECT

CLIENT:
FERMCO Fernald Environmental Restoration Management Corporation
FERNALD ENVIRONMENTAL RESTORATION MANAGEMENT CORPORATION

PROJECT:
ON-SITE DISPOSAL FACILITY 492

TITLE:
CHAIN LINK FENCE AND GATE DETAILS
24007_37

THIS DRAWING MAY NOT BE ISSUED FOR PROJECT TENDER OR CONSTRUCTION, UNLESS SEALED.

Rudolph Bonaparte
SIGNATURE
8 Oct 1996
DATE

STATE OF OHIO
RUDOLPH BONAPARTE
E-58679
REGISTERED PROFESSIONAL ENGINEER
SEAL

GeoSyntec Consultants
1100 LAKE HEARN DRIVE
ATLANTA, GEORGIA 30342 USA

FERMCO PROJECT NO.:	20100
FERMCO SUBCONTRACT NO.:	95PS005028
FERMCO DRAWING NO.:	90X-6000-S-00055
GEOSYNTEC PROJECT NO.:	GE3900-13.1
GEOSYNTEC DOCUMENT NO.:	F96-G165
SHEET NO.:	S-5
REVISION NO.:	G

FINAL DESIGN PACKAGE

M:\GAACAD2\GE3900-13\F96-G165 Mon Oct 07 06:48:49 1996 UNSLAM